

ZEROPERM A Tape

Product Overview



ZEROPERM® A Tape is available to complete installation in the field. It uses a high quality, acrylic adhesive with excellent cold weather performance. ZEROPERM® A Tape has a kraft release liner and is typically used for sealing longitudinal and circumferential laps. It is available in 2" and 3" wide rolls. Made from the same material as the ZEROPERM® Vapor Barrier, the tape maintains an absolute "zero perm" barrier that provides maximum protection for all types of insulations used in below ambient, sub-freezing and cryogenic applications on duct, pipe, or vessel systems.

ZEROPERM® Tapes are used as part of the ZEROPERM® Vapor Barrier System on cold pipe applications either between layers of insulation on sub-freezing projects like LNG piping, or as the outer vapor-barrier jacket on ammonia, brine or glycol systems under mechanical jacketing, either metal or PVC. ZEROPERM® can also be used on chilled water systems replacing ASJ and PVDC jacketing either left exposed or under a protective metal or PVC jacket.

Physical Property	Test Method	Zero-Perm A	Zero-Perm B
Total Product Thickness(w/o liner)	Micrometer	4.7 mils	3.7 mils
Thickness Carrier	Micrometer	3.4 mils	2.4 mils
Thickness Adhesive	Micrometer	1.3 mils	1.3 mils
Tensile Strength	PSTC 131	> 30 lbs/in	> 30lbs/in
Elongation	PSTC 131	64%	64%
Peel Adhesion	PSTC 101	39 oz/in	39oz/in
Minimum Application Temperature		10°F	10°F
Maximum Continuous Temp.		200°F	200°F



Meets ASTM E84 25/50 Smoke and Flame requirements



Absolute Zero permeability



Puncture and tear resistant



Mold resistant



Paper-free



Available in silver or white



2" and 3" wide rolls



Rolls are 150' long

contact us



3801 S. IH-45
Ennis, TX 75119

Phone : 214-515-5000

Web : www.polyguard.com

Social : @polyguardproducts

