

RG-2400 COVERAGE CHART BY PIPE SIZE

Save Time! – Save Money!

Use AccuTrowel™ for consistent coverage.

Approximately 60 SqFt/Gallon Coverage @ 25 MILS

COVERAGE—U.S.			25 MILS	25 MILS	30 MILS	40 MILS
IRON PIPE SIZE	PIPE OUTSIDE DIAMETER INCH	SQUARE FOOT PER LF	LINEAR FEET PER GALLON			
			HAND APPLIED	AccuTrowel™ APPLIED	HAND APPLIED	HAND APPLIED
1/4"	0.625	0.164	367	--	294	221
1/2"	0.875	0.229	263	--	211	158
3/4"	1.05	0.275	219	--	176	131
1"	1.375	0.36	167	--	134	101
1-1/4"	1.625	0.425	141	--	113	85
1-1/2"	1.9	0.497	122	--	97	73
2"	2.375	0.622	98	113	77	59
2-1/2"	2.875	0.753	80	92	64	48
3"	3.5	0.916	66	76	52	40
3-1/2"	4	1.047	58	67	46	34
4"	4.5	1.178	51	59	41	31
4-1/2"	5	1.309	46	53	37	28
5"	5.563	1.456	41	47	33	25
6"	6.625	1.734	35	40	28	21
8"	8.625	2.258	27	31	22	16
10"	10.75	2.814	20	23	17	13
12"	12.75	3.338	17	20	14	11
14"	14	3.665	16	--	14	10
16"	16	4.189	14	--	12	9
18"	18	4.713	12	--	10	8
20"	20	5.236	11	--	9	7
22"	22	5.76	10	--	8	6
24"	24	6.283	9	--	8	5



P.O. Box 755
Ennis, TX 75120
PH: (214) 515-5000
FX: (972) 875-9425

This information is based on our best knowledge, but
POLYGUARD cannot guarantee the results to be obtained.

Proud Member of
NIA | National Insulation
Association

www.polyguard.com/mechanical

RG-2400 COVERAGE CHART BY PIPE SIZE

Save Time! – Save Money!

Use AccuTrowel™ for consistent coverage.

Approximately 5.6 SqM/Gallon Coverage @ 25 MILS

COVERAGE—METRIC			25 MILS	25 MILS	30 MILS	40 MILS
IRON PIPE SIZE	PIPE OUTSIDE DIAMETER CM	SQUARE FOOT PER LF	METERS PER GALLON			
			HAND APPLIED	AccuTrowel™ APPLIED	HAND APPLIED	HAND APPLIED
1/4"	1.59	0.164	112	--	90	67
1/2"	2.22	0.229	80	--	64	48
3/4"	2.67	0.275	67	--	54	40
1"	3.49	0.36	51	--	41	31
1-1/4"	4.13	0.425	43	--	34	26
1-1/2"	4.83	0.497	37	--	30	22
2"	6.03	0.622	30	34	23	18
2-1/2"	7.30	0.753	24	28	20	15
3"	8.89	0.916	20	23	16	12
3-1/2"	10.16	1.047	18	20	14	10
4"	11.43	1.178	16	18	12	9
4-1/2"	12.70	1.309	14	16	11	9
5"	14.13	1.456	12	14	10	8
6"	16.83	1.734	11	12	9	6
8"	21.91	2.258	8	9	7	5
10"	27.31	2.814	6	7	5	4
12"	32.39	3.338	5	6	4	3
14"	35.56	3.665	5	--	4	3
16"	40.64	4.189	4	--	4	3
18"	45.72	4.713	4	--	3	2
20"	50.80	5.236	3	--	3	2
22"	55.88	5.76	3	--	2	2
24"	60.96	6.283	3	--	2	2



REV092425

P.O. Box 755
Ennis, TX 75120
PH: (214) 515-5000
FX: (972) 875-9425

This information is based on our best knowledge, but
POLYGUARD cannot guarantee the results to be obtained.

Proud Member of
NIA | National Insulation
Association

www.polyguard.com/mechanical