



BACKER ROD AND SEALANT
FOR CONTINUOUS AIR
BARRIER (BY OTHERS)

COMPRESSIBLE FOAM FILLER
BACKER ROD AND
SEALANT (BY OTHERS)

NON-FLANGED WINDOW, DOOR,
OR FIXTURE (WINDOW SHOWN)

CLOSE CAVITY AT JAMB
WITH MASONRY

POLYGUARD AIRLOK SHEET 200 BU SERIES OR AIRLOK SHEET 400 SERIES APPLIED OVER POLYGUARD 650 LT LIQUID ADHESIVE OR CALIFORNIA SEALANT APPLIED AT A RATE OF 250 - 300 SF / GAL, OR OVER 650 WB LIQUID ADHESIVE APPLIED AT A RATE OF 350 - 400 SF / GAL; OR POLYGUARD DETAIL SEALANT PW APPLIED AND TOOLED TO MINIMUM 25 MILS WET. EXTEND SELECTED FLASHING A MINIMUM 3" ONTO EACH SURFACE. APPLY SELECTED FLASHING EITHER BEFORE OR AFTER (AS SHOWN) SELECTED POLYGUARD AIR BARRIER MEMBRANE.

POLYGUARD NON-PERMEABLE AIRLOK SHEET 200 BU SERIES AIR BARRIER MEMBRANE APPLIED BEFORE (AS SHOWN) OR AFTER SELECTED FLASHING MEMBRANE

LOW-RISE SPRAY ADHESIVE (BY OTHERS)

RIGID INSULATION

04

PLAN @ FRAMED BACKING WALL / MASONRY VENEER - NON-FLANGED WINDOW, DOOR, OR FIXTURE JAMB

ASBNP

Polyguard Products, Inc. P.O. Box 755 - Ennis, TX 75120 Phone: 214-515-5000 Web Site - www.polyguard.com ©POLYGUARD PRODUCTS, INC. MATERIAL SEPARATED FOR CLARITY

The information provided is based on data and knowledge considered to be true and accurate and is offered for the users' consideration, investigation and verification, but we do not warrant the results to be obtained. Please read all data sheets, statements, recommendations or suggestions in conjunction with our conditions of sale, which about to all goods supplied to use

NOT TO SCALE EFFECTIVE DATE: 03/06/2023 SUPERCEDES:

01/01/2023