



- WOOD STUD FRAMING
- CONCRETE FOUNDATION WALL
- POLYGUARD TRM SEALANT APPLIED AND TOOLED TO MINIMUM 90 MILS OVER AND ALONG METAL COUNTER FLASHING TOP EDGE, AS WELL AS OVER EACH FASTENER HEAD
- POWDER ACTUATED FASTENER (BY OTHERS)
- POLYGUARD TRM FLASHING OR TRM UV2-40 FLASHING, CUT BACK 1/2" FROM EDGE
- POLYGUARD TRM SEALANT 1/2" BEAD CAULKED ON TOP OF TRM FLASHING
- METAL COUNTER FLASHING (BY OTHERS)
- POLYGUARD 650 TRM OVER CLEAN, DRY, FROST-FREE CONCRETE FOUNDATION WALL PREPARED WITH POLYGUARD 650 LT LIQUID ADHESIVE OR CALIFORNIA SEALANT APPLIED AT A RATE OF 250 - 300 SF / GAL, OR OVER 650 WB LIQUID ADHESIVE APPLIED AT A RATE OF 350 - 400 SF / GAL
- GROUT FILLED CAVITY
- POLYGUARD LM-95 OR DETAIL SEALANT PW APPLIED AND TOOLED OVER CLEAN AND DRY CONCRETE TO MINIMUM 3/4" CANT / FILLET
- BRICK OR MASONRY VENEER
- POLYGUARD 650 TRM STRIP, OR TRM FLASHING, APPLIED OVER ALL INSIDE AND OUTSIDE CORNERS; APPLY OVER CLEAN, DRY, FROST-FREE SUBSTRATES PREPARED WITH POLYGUARD 650 LT LIQUID ADHESIVE OR CALIFORNIA SEALANT APPLIED AT A RATE OF 250 - 300 SF / GAL, OR OVER 650 WB LIQUID ADHESIVE APPLIED AT A RATE OF 350 - 400 SF / GAL

**AT1**

**SECTION @ TRM FLASHING - THRU-WALL FLASHING INSTALLATION**

**GENERAL NOTE: IF ADHESIVE IS REQUIRED FOR SEAMS OR END LAPS, DO NOT USE POLYGUARD 650 WB LIQUID ADHESIVE.**

MATERIAL SEPARATED FOR CLARITY  
© POLYGUARD PRODUCTS, INC.

<small>The information provided is based on data and knowledge considered to be true and accurate and is offered for the users' consideration, investigation and verification, but we do not warrant the results to be obtained. Please read all data sheets, statements, recommendations or suggestions in conjunction with our conditions of sale, which apply to all goods supplied by us.</small>	NOT TO SCALE
	EFFECTIVE DATE: 01/06/2025
	SUPERCEDES: 11/08/2018