




APPROVED RETENTION SYSTEM - BY OTHERS

POLYGUARD POLYFLOW 15 / 15P SHEET MOLDED DRAIN FABRIC FACING RETENTION SYSTEM

PENETRATION SIDEWALLS ABRAIDED AND PREPARED WITH POLYGUARD 650 LT LIQUID ADHESIVE OR POLYGUARD CALIFORNIA SEALANT APPLIED AT A RATE OF 250 - 300 SF/GAL

6"

POLYGUARD BLINDSIDE MEMBRANE FABRIC TOWARD CONCRETE POUR



POLYGUARD DETAIL SEALANT PW OR POLYGUARD LM-95 APPLIED TO TOP PERIMETER OF PATCH AND EXISTING MEMBRANE PREPARED WITH POLYGUARD 650 LT LIQUID ADHESIVE OR POLYGUARD CALIFORNIA SEALANT AT A RATE OF 50 - 75 SF/GAL

MINIMUM 90 MILS OF POLYGUARD LM-95 APPLIED 3" ONTO PENETRATION AND POLYGUARD BLINDSIDE MEMBRANE MINIMUM 6" PREPARE FABRIC WITH POLYGUARD 650 LT LIQUID ADHESIVE OR POLYGUARD CALIFORNIA SEALANT APPLIED AT A RATE OF 50 - 75 SF/GAL

SEALANT AND BACKER ROD - BY OTHERS

POLYGUARD BLINDSIDE MEMBRANE OVERLAY TIGHTLY FIT AROUND PENETRATION SIDEWALLS AND EXTENDED ONTO THE FIELD MEMBRANE A MINIMUM OF 6"

POLYGUARD FABRIC TAPE CENTERED AROUND PERIMETER OF POLYGUARD BLINDSIDE MEMBRANE PATCH PREPARED WITH POLYGUARD 650 LT LIQUID ADHESIVE OR POLYGUARD CALIFORNIA SEALANT AT A RATE OF 50 - 75 SF/GAL



## SECTION @ PENETRATION ROUGH FIT AROUND PENETRATION SIDEWALL

**Δ**.

. 4

©POLYGUARD PRODUCTS, INC. MATERIAL SEPARATED FOR CLARITY

Polyguard Products, Inc. P.O. Box 755 - Ennis, TX 75120 Phone: 214-515-5000 Web Site - www.polyguard.com The information provided is based on data and knowledge considered to be true and accurate and is offered for the users' consideration, investigation and verification, but we do not warrant the results to be obtained. Please read all data sheets, statements, recommendations or suggestions in conjunction with our conditions of sale, which apply to all goods supplied by users.

EFFECTIVE DATE: 12/16/2024 SUPERCEDES: 07/15/2024

NOT TO SCALE