





SEAL TOP EDGE OF POLYGUARD 105 FLASHING AND ALL SEAMS OF POLYGUARD BALCONY SHEET MEMBRANE SERIES WATERPROOFING WITH POLYGUARD DETAIL SEALANT PW OR POLYGUARD LM-95 APPLIED AND TOOLED TO MINIMUM 60-MILS, EXTEND MINIMUM 1" ON EACH SIDE OF JOINT

POLYGUARD 105 FLASHING APPLIED TO SUBSTRATE PREPARED WITH POLYGUARD 650 LT LIQUID ADHESIVE OR POLYGUARD CALIFORNIA SEALANT APPLIED AT A RATE OF 250 - 300 SF / GAL OR POLYGUARD 650 WB LIQUID ADHESIVE APPLIED AT A RATE OF 350 - 400 SF / GAL - CAN BE APPLIED BEFORE OR AFTER FIELD MEMBRANE DEPENDING ON CONSTRUCTION SEQUENCE

POLYGUARD BALCONY SHEET MEMBRANE SERIES
WATERPROOFING APPLIED TO SUBSTRATE PREPARED WITH
POLYGUARD 650 LT LIQUID ADHESIVE OR POLYGUARD CALIFORNIA
SEALANT APPLIED AT A RATE OF 250 - 300 SF / GAL OR POLYGUARD
650 WB LIQUID ADHESIVE APPLIED AT A RATE OF 350 - 400 SF / GAL

POLYGUARD BG OUTSIDE CORNER BOOT APPLIED TO SUBSTRATE PREPARED WITH POLYGUARD 650 LT LIQUID ADHESIVE OR POLYGUARD CALIFORNIA SEALANT APPLIED AT A RATE OF 250 - 300 SF / GAL OR POLYGUARD 650 WB LIQUID ADHESIVE APPLIED AT A RATE OF 350 - 400 SF / GAL ,OR POLYGUARD DETAIL SEALANT PW OR POLYGUARD LM-95 APPLIED AND TOOLED TO MINIMUM 60 MILS EXTENDED MINIMUM 6" IN EACH DIRECTION FROM CORNER

BEAD OF POLYGUARD DETAIL SEALANT PW OR POLYGUARD LM-95 APPLIED TO TERMINATION OF MEMBRANE STRIP REFERENCE EDGE DETAIL

DRIP EDGE - BY OTHERS

STRIP OF POLYGUARD BALCONY SHEET MEMBRANE SERIES WATERPROOFING OVER POLYGUARD 650 LT LIQUID ADHESIVE OR POLYGUARD CALIFORNIA SEALANT APPLIED AT A RATE OF 250 - 300 SF/GAL OR POLYGUARD 650 WB LIQUID ADHESIVE APPLIED AT A RATE OF 350 - 400 SF/GAL EXTENDING BEYOND DRIP EDGE 2" FOR ADHESION OF FIELD MEMBRANE - REFERENCE EDGE DETAIL

4" X 4" 60-MIL ELASTOMERIC SHIM @ 18" O.C. MAX AS SPECIFIED - BY OTHERS

CONCRETE T-RAIL AT BALCONY EDGE - BY OTHERS CONCRETE SLAB - BY OTHERS

ISOMETRIC @ OVERVIEW ZERO SLOPE BALCONY DECK

Polyguard Products, Inc. P.O. Box 755 - Ennis, TX 75120 Phone: 214-515-5000 Web Site - www.polyguard.com

BW4

SPECIAL NOTE: IF ADHESIVE IS REQUIRED FOR SEAMS OR END LAPS, DO NOT USE POLYGUARD 650 WB LIQUID ADHESIVE

©POLYGUARD PRODUCTS, INC.
MATERIAL SEPARATED FOR CLARITY

The information provided is based on data and knowledge considered to be true and accurate and is offered for the users' consideration, investigation and verification, but we do not warrant the results to be obtained. Please read all data sheets, statements, recommendations or suggestions in coniunction with our conditions of sale, which apoly to all cooks supplied but which apoly to all cooks supplied but the conditions of sale which apoly to all cooks supplied but the conditions of sale which apoly to all cooks supplied but the conditions of the conditions of sale which apoly to all cooks supplied but the conditions of the conditions of sale which apoly to all conditions of sale which apoly to all conditions of the conditions of sale which are the conditions of th

NOT TO SCALE

EFFECTIVE DATE:
04/20/2023
SUPERCEDES:
10/01/2022