





SEAL TOP EDGE OF POLYGUARD 105 FLASHING AND ALL SEAMS OF POLYGUARD BALCONY SHEET MEMBRANE SERIES WATERPROOFING WITH POLYGUARD DETAIL SEALANT PW OR POLYGUARD LM-95 APPLIED AND TOOLED - REFER TO BW 6

POLYGUARD 105 FLASHING APPLIED TO SUBSTRATE PREPARED WITH POLYGUARD 650 LT LIQUID ADHESIVE OR POLYGUARD CALIFORNIA SEALANT APPLIED AT A RATE OF 250 - 300 SF / GAL OR POLYGUARD 650 WB LIQUID ADHESIVE APPLIED AT A RATE OF 350 - 400 SF / GAL - CAN BE APPLIED BEFORE OR AFTER FIELD MEMBRANE DEPENDING ON CONSTRUCTION SEQUENCE

POLYGUARD BALCONY SHEET MEMBRANE SERIES WATERPROOFING APPLIED TO SUBSTRATE PREPARED WITH POLYGUARD 650 LT LIQUID ADHESIVE OR POLYGUARD CALIFORNIA SEALANT APPLIED AT A RATE OF 250 - 300 SF / GAL OR POLYGUARD 650 WB LIQUID ADHESIVE APPLIED AT A RATE OF 350 - 400 SF / GAL

POLYGUARD BG OUTSIDE CORNER BOOT APPLIED TO SUBSTRATE PREPARED WITH POLYGUARD 650 LT LIQUID ADHESIVE OR POLYGUARD CALIFORNIA SEALANT APPLIED AT A RATE OF 250 - 300 SF / GAL OR POLYGUARD 650 WB LIQUID ADHESIVE APPLIED AT A RATE OF 350 - 400 SF / GAL ,OR POLYGUARD DETAIL SEALANT PW OR POLYGUARD LM-95 APPLIED AND TOOLED EXTENDED MINIMUM 6" IN EACH DIRECTION FROM CORNER - REFER TO BW 6

BEAD OF POLYGUARD DETAIL SEALANT PW OR POLYGUARD LM-95 APPLIED TO TERMINATION OF MEMBRANE STRIP REFERENCE - REFER TO BW6

DRIP EDGE - BY OTHERS

STRIP OF POLYGUARD BALCONY SHEET MEMBRANE SERIES WATERPROOFING OVER POLYGUARD 650 LT LIQUID ADHESIVE OR POLYGUARD CALIFORNIA SEALANT APPLIED AT A RATE OF 250 - 300 SF/GAL OR POLYGUARD 650 WB LIQUID ADHESIVE APPLIED AT A RATE OF 350 - 400 SF/GAL EXTENDING BEYOND DRIP EDGE 2" FOR ADHESION OF FIELD MEMBRANE - REFERENCE EDGE DETAIL

4" X 4" 60-MIL ELASTOMERIC SHIM @ 18" O.C. MAX AS SPECIFIED - BY OTHERS

CONCRETE T-RAIL AT BALCONY EDGE - BY OTHERS CONCRETE SLAB - BY OTHERS

ISOMETRIC @ OVERVIEW ZERO SLOPE BALCONY DECK

TOOMETINO & OVERVIEW ZEINO CEGI E BALCONYI E

Polyguard Products, Inc. P.O. Box 755 - Ennis, TX 75120 Phone: 214-515-5000 Web Site - www.polyguard.com

BW4

SPECIAL NOTE: IF ADHESIVE IS REQUIRED FOR SEAMS OR END LAPS, DO NOT USE POLYGUARD 650 WB LIQUID ADHESIVE

©POLYGUARD PRODUCTS, INC.
MATERIAL SEPARATED FOR CLARITY

The information provided is based on data and knowledge considered to be true and accurate and is offered for the users' consideration, investigation and verification, but we do not warrant the results to be obtained. Please read all data sheets, statements, recommendations or suggestions in conlunction with our conditions of sale, which apoly to all cooks supplied by use

NOT TO SCALE

EFFECTIVE DATE:
07/16/2024

SUPERCEDES:
06/06/2023