



POLYGUARD DETAIL SEALANT PW OR LM-95 APPLIED OVER ALL POLYGUARD 105 FLASHING WATERPROOFING EDGES AND SEAMS; TOOL SELECTED SEALANT OVER JOINT AT A CONTINUOUS MINIMUM 115 MILS THICK; EXTEND SELECTED SEALANT A CONTINUOUS MINIMUM 10 MILS THICK TO MINIMUM 3/4" ON EACH SIDE OF JOINT

POLYGUARD DETAIL SEALANT PW OR LM-95 APPLIED OVER ALL POLYGUARD BALCONY MEMBRANE SERIES WATERPROOFING EDGES AND SEAMS; TOOL SELECTED SEALANT OVER JOINT AT A CONTINUOUS MINIMUM 70 MILS THICK; EXTEND SELECTED SEALANT A CONTINUOUS MINIMUM 10 MILS THICK TO MINIMUM 3/4" ON EACH SIDE OF JOINT

POLYGUARD BALCONY MEMBRANE SERIES WATERPROOFING APPLIED TO SUBSTRATE PREPARED WITH POLYGUARD 650 LT LIQUID ADHESIVE OR CALIFORNIA SEALANT APPLIED AT A RATE OF 250 - 300 SF / GAL, OR OVER 650 WB LIQUID ADHESIVE APPLIED AT A RATE OF 350 - 400 SF / GAL; INSTALL IN SHINGLE MANNER WITH MINIMUM 9" OVERLAP

POLYGUARD 105 FLASHING APPLIED TO SUBSTRATE PREPARED WITH POLYGUARD 650 LT LIQUID ADHESIVE OR CALIFORNIA SEALANT APPLIED AT A RATE OF 250 - 300 SF / GAL OR 650 WB LIQUID ADHESIVE APPLIED AT A RATE OF 350 - 400 SF / GAL - CAN BE APPLIED BEFORE OR AFTER FIELD MEMBRANE DEPENDING ON CONSTRUCTION SEQUENCE

POLYGUARD DETAIL SEALANT PW OR LM-95 APPLIED AND TOOLED TO MINIMUM 60-MILS, EXTEND MINIMUM 3/4" ON EACH SIDE OF JOINT

LIVE LOADING AND CREEP REQUIREMENTS: CONSULT WITH STRUCTURAL ENGINEER ABOUT CONSTRUCTION AND MAINTENANCE OF 1/8-INCH POSITIVE SLOPE FOR DRAINAGE OF STRUCTURAL DECK

**BW6**

**SECTION @ BALCONY MEMBRANE SERIES WATERPROOFING - OVERLAP / EDGE OVERVIEW (ZERO SLOPE)**

**GENERAL NOTE: IF ADHESIVE IS REQUIRED FOR SEAMS OR END LAPS, DO NOT USE POLYGUARD 650 WB LIQUID ADHESIVE.**

MATERIAL SEPARATED FOR CLARITY  
© POLYGUARD PRODUCTS, INC.

The information provided is based on data and knowledge considered to be true and accurate and is offered for the users' consideration, investigation and verification, but we do not warrant the results to be obtained. Please read all data sheets, statements, recommendations or suggestions in conjunction with our conditions of sale, which apply to all goods supplied by us.	NOT TO SCALE
	EFFECTIVE DATE: 06/07/2023
	SUPERCEDES: NONE