





CONCRETE SLAB - BY OTHERS

POLYGUARD BALCONY SHEET MEMBRANE SERIES WATERPROOFING FIELD SHEET APPLIED OVER POLYGUARD 650 LT LIQUID ADHESIVE OR POLYGUARD CALIFORNIA SEALANT APPLIED AT A RATE OF 250 - 300 SF / GAL, OR OVER POLYGUARD 650 WB LIQUID ADHESIVE APPLIED AT A RATE OF 350 - 400 SF / GAL

EXTRUDED CONCRETE T-RAIL, SCREW WITH DRIP EDGE TO DECK - BY OTHERS

THIS TIE-IN DIMENSION CAN BE GREATER TO ACCOMMODATE RAILING INSTALLATION DISCUSSIONS

60-MIL ELASTOMERIC SHIM - BY OTHERS

POLYGUARD DETAIL SEALANT PW OR POLYGUARD LM-95 TOOLED AND FEATHERED AS TERMINATION EDGE SEAL - REFER TO BW3 OR 6

POLYGUARD BALCONY SHEET MEMBRANE SERIES WATERPROOFING STARTER STRIP APPLIED HORIZONTALLY WITH VERTICAL TURNDOWN LEG OVER POLYGUARD 650 LT LIQUID ADHESIVE OR POLYGUARD CALIFORNIA SEALANT APPLIED AT A RATE OF 250 - 300 SF / GAL, OR OVER POLYGUARD 650 WB LIQUID ADHESIVE APPLIED AT A RATE OF 350 - 400 SF / GAL; EXTEND BEYOND DRIP EDGE MINIMUM 2" FOR TIE-IN ADHESION OF POLYGUARD BALCONY SHEET MEMBRANE SERIES WATERPROOFING FIELD SHEET AS SECONDARY WATERPROOFING SEAL

DO NOT USE SEALANT AT THIS LOCATION

DRIP EDGE - BY OTHERS

EXTERIOR FACADE - STUCCO SHOWN - BY OTHERS

MECHANICALLY-ATTACHED SHEET AIR BARRIER MEMBRANE - BY OTHERS

SECTION @ EDGE DETAIL - (OPTION 1)

Polyguard Products, Inc. P.O. Box 755 - Ennis, TX 75120 Phone: 214-515-5000 Web Site - www.polyguard.com

BW7a

SPECIAL NOTE: IF ADHESIVE IS REQUIRED FOR SEAMS OR ENDLAPS DO NOT USE POLYGUARD 650 WB LIQUID ADHESIVE ©POLYGUARD PRODUCTS, INC. MATERIAL SEPARATED FOR CLARITY

The information provided is based on data and knowledge considered to be true and accurate and is offered for the users' consideration, investigation and verification, but we do not warrant the results to be obtained. Please read all data sheets, statements, recommendations or suggestions in conjunction with our conditions of sale, which apply to all goods supplied by use

NOT TO SCALE

EFFECTIVE DATE:
07/15/2024

SUPERCEDES:

06/06/2023