



CONCRETE SLAB - BY OTHERS

POLYGUARD BALCONY SHEET MEMBRANE SERIES WATERPROOFING FIELD SHEET APPLIED OVER POLYGUARD 650 LT LIQUID ADHESIVE OR POLYGUARD CALIFORNIA SEALANT APPLIED AT A RATE OF 250 - 300 SF / GAL, OR POLYGUARD 650 WB LIQUID ADHESIVE APPLIED AT A RATE OF 350 - 400 SF / GAL

THIS TIE-IN DIMENSION CAN BE GREATER TO ACCOMMODATE RAILING INSTALLATION DISCUSSIONS

60-MIL ELASTOMERIC SHIM - BY OTHERS

POLYGUARD DETAIL SEALANT PW OR POLYGUARD LM-95 APPLIED AND TOOLED FROM 30 MILS TO ZERO AS A FEATHERED EDGE, EXTEND A MINIMUM 1" ONTO EACH SIDE OF POLYGUARD BALCONY SHEET MEMBRANE SERIES WATERPROOFING FIELD SHEET AS TERMINATION EDGE SEAL

EXTRUDED CONCRETE T-RAIL, SCREW WITH DRIP EDGE TO DECK - BY OTHERS

DRIP EDGE - BY OTHERS

WET-SET DRIP EDGE INTO POLYGUARD DETAIL SEALANT PW OR POLYGUARD LM-95 APPLIED HORIZONTALLY ONLY AND TOOLED TO MINIMUM 30 MILS THICK; EXTEND BEYOND DRIP EDGE MINIMUM 2" FOR TIE-IN ADHESION OF POLYGUARD BALCONY SHEET MEMBRANE SERIES WATERPROOFING FIELD MEMBRANE AS SECONDARY WATERPROOFING SEAL

MECHANICALLY-ATTACHED SHEET AIR BARRIER MEMBRANE - BY OTHERS

EXTERIOR FACADE - STUCCO SHOWN - BY OTHERS



SECTION @ EDGE DETAIL - (OPTION 2)

Polyguard Products, Inc. P.O. Box 755 - Ennis, TX 75120 Phone: 214-515-5000 Web Site - www.polyguard.com

SPECIAL NOTE: IF ADHESIVE IS REQUIRED FOR SEAMS OR ENDLAPS DO NOT USE POLYGUARD 650 WB LIQUID ADHESIVE ©POLYGUARD PRODUCTS, INC. MATERIAL SEPARATED FOR CLARITY

The information provided is based on data and knowledge considered to be true and accurate and is offered for the users' consideration, investigation and verification, but we do not warrant the results to be obtained. Please read all data sheets, statements, recommendations or suggestions in conjunction with our conditions of sale, which apply to all goods supplied by us

NOT TO SCALE

On EFFECTIVE DATE:
10/01/2022
SUPERCEDES:

11/08/2021