


STEP 3

BALCONY SUBSTRATE SHEATHING WALL - BY OTHERS


MECHANICALLY ATTACHED SHEET AIR BARRIER AND EDGE TAPE BY OTHERS APPLIED PER AIR BARRIER MANUFACTURER INSTALLATION GUIDELINES. HOLD MATERIAL MINIMUM 2" FROM BALCONY FLOOR EDGE FOR OVERLAP / TIE-IN OF POLYGUARD BALCONY SHEET MEMBRANE WATERPROOFING MATERIALS

POLYGUARD DETAIL TAPE FLASHING (PIECE #1) OVER CLEAN AND DRY SUBSTRATES PREPARED WITH POLYGUARD 650 LT LIQUID ADHESIVE OR POLYGUARD CALIFORNIA SEALANT AT A RATE OF 250 - 300 SF / GAL, OR POLYGUARD 650 WB LIQUID ADHESIVE AT A RATE OF 350 - 400 SF / GAL



POLYGUARD DETAIL TAPE FLASHING (PIECE #2) OVER CLEAN AND DRY SUBSTRATES PREPARED WITH POLYGUARD 650 LT LIQUID ADHESIVE OR POLYGUARD CALIFORNIA SEALANT AT A RATE OF 250 - 300 SF / GAL, OR POLYGUARD 650 WB LIQUID ADHESIVE AT A RATE OF 350 - 400 SF / GAL

POLYGUARD 105 FLASHING APPLIED TO SUBSTRATES PREPARED WITH POLYGUARD 650 LT LIQUID ADHESIVE OR POLYGUARD CALIFORNIA SEALANT AT A RATE OF 250 - 300 SF / GAL, OR POLYGUARD 650 WB LIQUID ADHESIVE AT A RATE OF 350 - 400 SF / GAL





6"

ISOMETRIC @ FIELD-FORMED CORNER FLASHING POLYGUARD STARTER STRIP STEPS 1 - 4

©POLYGUARD PRODUCTS, INC. MATERIAL SEPARATED FOR CLARITY

Polyguard Products, Inc. P.O. Box 755 - Ennis. TX 75120 Phone: 214-515-5000 Web Site - www.polyguard.com

SPECIAL NOTE: IF ADHESIVE IS REQUIRED FOR SEAMS OR ENDLAPS DO NOT USE POLYGUARD 650 WB LIQUID ADHESIVE

NOT TO SCALE The information provided is based on data and knowledge considered to be true and accurate and is offered for the users' consideration, investigation and verification, but we do not warrant the results to be obtained. Please read all data sheets, statements, recommendations or suggestions in conjunction with our conditions of sale, which apply to all goods supplied by us

EFFECTIVE DATE: 10/01/2022 SUPERCEDES: 06/14/2021