



BALCONY SUBSTRATE SHEATHING WALL

MECHANICALLY ATTACHED SHEET AIR BARRIER INSTALLED PER MANUFACTURER INSTALLATION **GUIDELINES - BY OTHERS**


MECHANICALLY ATTACHED SHEET AIR BARRIER WITH A SELF ADHERED FLASHING TAPE - BY OTHERS MUST BE PRE-APPROVED BY POLYGUARD, PROVIDE MINIMUM 6" HORIZONTAL LEG FOR POLYGUARD BALCONY SHEET MEMBRANE SERIES WATERPROOFING AND DRIP EDGE OVERLAY IN SUBSEQUENT STEPS





POLYGUARD DETAIL TAPE FLASHING (PIECE #1) OVER CLEAN AND DRY SUBSTRATES PREPARED WITH POLYGUARD 650 LT LIQUID ADHESIVE OR POLYGUARD CALIFORNIA SEALANT AT A RATE OF 250 - 300 SF / GAL, OR POLYGUARD 650 WB LIQUID ADHESIVE APPLIED AT A RATE OF 350 - 400 SF / GAL

POLYGUARD DETAIL TAPE FLASHING (PIECE #2) OVER CLEAN AND DRY SUBSTRATES PREPARED WITH POLYGUARD 650 LT LIQUID ADHESIVE OR POLYGUARD CALIFORNIA SEALANT AT A RATE OF 250 - 300 SF / GAL, OR POLYGUARD 650 WB LIQUID ADHESIVE APPLIED AT A RATE OF 350 - 400 SF / GAL





ISOMETRIC @ FIELD-FORMED CORNER FLASHING AIR BARRIER STARTER STRIP STEPS 1 - 4

©POLYGUARD PRODUCTS, INC. MATERIAL SEPARATED FOR CLARITY