



BALCONY SUBSTRATE SHEATHING WALL

MECHANICALLY ATTACHED SHEET AIR BARRIER INSTALLED PER MANUFACTURER INSTALLATION **GUIDELINES - BY OTHERS**


MECHANICALLY ATTACHED SHEET AIR BARRIER WITH A SELF ADHERED FLASHING TAPE - BY OTHERS MUST BE PRE-APPROVED BY POLYGUARD, PROVIDE MINIMUM 6" HORIZONTAL LEG FOR POLYGUARD BALCONY SHEET MEMBRANE SERIES WATERPROOFING AND DRIP EDGE OVERLAY IN SUBSEQUENT STEPS





POLYGUARD DETAIL TAPE FLASHING (PIECE #1) OVER CLEAN AND DRY SUBSTRATES PREPARED WITH POLYGUARD 650 LT LIQUID ADHESIVE OR POLYGUARD CALIFORNIA SEALANT AT A RATE OF 250 - 300 SF / GAL, OR POLYGUARD 650 WB LIQUID ADHESIVE APPLIED AT A RATE OF 350 - 400 SF / GAL

POLYGUARD DETAIL TAPE FLASHING (PIECE #2) OVER CLEAN AND DRY SUBSTRATES PREPARED WITH POLYGUARD 650 LT LIQUID ADHESIVE OR POLYGUARD CALIFORNIA SEALANT AT A RATE OF 250 - 300 SF / GAL, OR POLYGUARD 650 WB LIQUID ADHESIVE APPLIED AT A RATE OF 350 - 400 SF / GAL





ISOMETRIC @ FIELD-FORMED CORNER FLASHING AIR BARRIER STARTER STRIP STEPS 1 - 4

©POLYGUARD PRODUCTS, INC. MATERIAL SEPARATED FOR CLARITY

Polyguard Products, Inc. P.O. Box 755 - Ennis, TX 75120 Phone: 214-515-5000 Web Site - www.polyguard.com

SPECIAL NOTE: IF ADHESIVE IS REQUIRED FOR SEAMS OR ENDLAPS DO NOT USE POLYGUARD 650 WB LIQUID ADHESIVE

NOT TO SCALE The information provided is based on data and knowledge considered to be true and accurate and is offered for the users' consideration, investigation and verification, but we do not warrant the results to be obtained. Please read all data sheets, statements, recommendations or suggestions in conjunction with our conditions of sale, which apply to all goods supplied by us

EFFECTIVE DATE: 10/01/2022 SUPERCEDES: 06/14/2021