

FACTORY SEAM

INSTALL POLYGUARD CR PIT TOP CORNER BOOT INTERFACING WITH THE ADHESIVE OF THE POLYGUARD CR SEAM TAPE

POLYGUARD UNDERSEAL CR SEAM TAPE

PIT WALL SUBSTRATE (POLYGUARD POLYFLOW 15 , SLURRY WALL, ETC.)




IMAGE 2

ROUGH-FIT THE FIELD SHEET OF THE POLYGUARD CRM MEMBRANE AROUND THE TOP OF THE PIT WALLS





IMAGE 3

PREPARE THE
POLYGUARD CRM
MEMBRANE FIELD
SHEET WITH
POLYGUARD CR
SEALANT AND THEN
POLYGUARD CR LIQUID
MEMBRANE TO WET
SET THE POLYGUARD
CRM MEMBRANE
OVERLAP

INSTALL POLYGUARD
UNDERSEAL CRM ONTO
THE PIT SIDEWALL AND
A MINIMUM 6" ONTO
THE UNDERSEAL CRM
FIELD SHEET AROUND
THE TOP OF THE PIT



POLYGUARD FABRIC TAPE, EXTEND 6" TO EACH SIDE OF THE POLYGUARD CRM MEMBRANE END LAP

- 6 PREPARE & CLEAN THE POLYGUARD CRM MEMBRANE FABRIC 6" TO EACH SIDE OF THE END LAP
- 7 APPLY POLYGUARD CR SEALANT TO THE CLEANED AREA AT THE RATE OF 50-75 SF / GAL
- 8 COVER THE POLYGUARD CR SEALANT WITH POLYGUARD FABRIC TAPE
- 9 ROLL THE POLYGUARD FABRIC TAPE WITH A 75-LB HARD SURFACE ROLLER

CRH20

SECTION @ CRM MEMBRANE PIT SIDEWALL TRANSITION AT TOP OF WALL

©POLYGUARD PRODUCTS, INC. MATERIAL SEPARATED FOR CLARITY

Polyguard Products, Inc. P.O. Box 755 - Ennis, TX 75120 Phone: 214-515-5000 Web Site - www.polyguard.com The information provided is based on data and knowledge considered to be true and accurate and is offered for the users' consideration, investigation and verification, but we do not warrant the results to be obtained. Please read all data sheets, statements, recommendations or suggestions in conjunction with our conditions of sale, which apply to all goods supplied by use

NOT TO SCALE

EFFECTIVE DATE:
07/15/2024

SUPERCEDES:
10/01/2022