



FIELD SHEET OF POLYGUARD PRM MEMBRANE

REPAIR DAMAGED AREAS, FISHMOUTH AND BUBBLES LARGER THAN 4" IN DIAMETER. REMOVE ANY MATERIAL THAT DOES NOT ALLOW PATCH TO BE FULLY ADHERED OR LAY FLAT

APPLY A PATCH OF POLYGUARD PRM MEMBRANE 6" LARGER THAN DAMAGE IN ALL DIRECTIONS TO EXISTING MEMBRANE PREPARED WITH POLYGUARD 650 LT LIQUID ADHESIVE OR POLYGUARD CALIFORNIA SEALANT APPLIED AT A RATE OF 250 - 300 SF/GAL OR POLYGUARD 650 WB LIQUID ADHESIVE AT A RATE OF 350 - 400 SF/GAL

POLYGUARD DETAIL SEALANT PW OR POLYGUARD LM-95 LIQUID MEMBRANE APPLIED TO PATCH PERIMETER EDGES TO 30 MIL THICKNESS AND 1" TO EACH SIDE OF THE EDGE

PRM1 OVERVIEW @ SELF-ADHERED REPAIR PATCH

Polyguard Products, Inc.
P.O. Box 755 - Ennis, TX 75120
Phone: 214-515-5000
Web Site - www.polyguard.com

SPECIAL NOTE: IF ADHESIVE IS REQUIRED FOR SEAMS OR ENDLAPS DO NOT USE POLYGUARD 650 WB LIQUID ADHESIVE

©POLYGUARD PRODUCTS, INC.
MATERIAL SEPARATED FOR CLARITY

<small>The information provided is based on data and knowledge considered to be true and accurate and is offered for the users' consideration, investigation and verification, but we do not warrant the results to be obtained. Please read all data sheets, statements, recommendations or suggestions in conjunction with our conditions of sale, which apply to all goods supplied by us.</small>	NOT TO SCALE
	EFFECTIVE DATE: 10/01/2022
	SUPERCEDES: 05/05/2022