





BRICK VENEER - BY OTHERS

RIGID INSULATION APPLIED OVER POLYGUARD STRETCH FLEX WITH LOW RISE SPRAY ADHESIVE - BY OTHERS

MASONRY WALL TIE - BY OTHERS

POLYGUARD STRETCH FLEX WATERPROOFING MEMBRANE APPLIED AT 27 SF/GAL (60 MILS WET) OVER CLEAN, DRY, AND RAW CONCRETE SUBSTRATE SURFACE

TERMINATION BAR (BY OTHERS) FOR SHEET THRU-WALL FLASHING ONLY. APPLY AND TOOL WITH POLYGUARD DETAIL SEALANT PW ALONG TOP EDGE AND OVER EACH FASTENER HEAD. TERMINATION BAR AND SEALANT ARE NOT REQUIRED IN COMBINATION WITH FLUID-APPLIED THRU-WALL FLASHING MATERIALS.

POLYGUARD DETAIL SEALANT PW TOOLED TO 25 MILS WET APPLIED OVER POLYGUARD STRETCH FLEX; OR POLYGUARD AIRLOK SHEET 200 BU / NP, AIRLOK SHEET 400 NP, AIRLOK SHEET 400 HT / NP OR AIRLOK SHEET UV 400 TO SUBSTRATE NOT UTILIZING THE STRETCH FLEX - WHEN USING POLYGUARD AIRLOK SHEET 400 NP, 400 HT/NP OR UV 400 APPLY POLYGUARD 650 LT LIQUID ADHESIVE OR POLYGUARD CALIFORNIA SEALANT APPLIED AT A RATE OF 250 - 300 SF / GAL , OR OVER POLYGUARD 650 WB LIQUID ADHESIVE APPLIED AT A RATE OF 350 - 400 SF / GAL PRIOR TO APPLICATION OF FLASHING (END DAMS NOT SHOWN). TERMINATE / TRIM SELECTED FLASHING 5/8" FROM BEND IN COUNTER FLASHING.

POLYGUARD DETAIL SEALANT PW APPLIED AND TOOLED TO FORM A 3/4" CANT WEEP HOLES (BEYOND) - BY OTHERS

COUNTER FLASHING (BY OTHERS) FOR UV PROTECTION

LINE OF GRADE

POLYGUARD POLYFLOW 15 / 15P MOLDED SHEET DRAIN WITH FABRIC FACING BACKFILL MATERIAL

POLYGUARD STRETCH FLEX WATERPROOFING MEMBRANE APPLIED AT 27 SF/GAL (60 MILS WET) OVER CLEAN, DRY, AND RAW CONCRETE SUBSTRATE SURFACE

SFBG01

SECTION @ CONCRETE FOUNDATION WALL - WALL BASE

©POLYGUARD PRODUCTS, INC. MATERIAL SEPARATED FOR CLARITY

The information provided is based on data and knowledge considered to be true and accurate and is offered for the users' consideration, investigation and verification, but we do not warrant the results to be obtained. Please read all data sheets, statements, recommendations or suggestions in conjunction with our conditions of sale, which apply to all goods supplied by us

NOT TO SCALE

EFFECTIVE DATE:
07/15/2024

SUPERCEDES:
03/20/2023

Polyguard Products, Inc. P.O. Box 755 - Ennis, TX 75120 Phone: 214-515-5000 Web Site - www.polyguard.com