



12" PIECE OF POLYGUARD FABRIC TAPE A MINIMUM 6" IN ALL DIRECTIONS PAST ENDLAP APPLIED TO CLEAN, DRY POLYGUARD UNDERSLAB MEMBRANE PREPARED WITH POLYGUARD 650 LT LIQUID ADHESIVE OR POLYGUARD CALIFORNIA SEALANT APPLIED AT A RATE OF 50 - 75 SF/GAL

OVERLAPPED END LAP OF POLYGUARD UNDERSLAB MEMBRANE FIELD SHEET

4" SELVEDGE EDGE

3" MINIMUM 4" MAXIMUM ENDLAP

US2 ISOMETRIC @ END LAP SEAM

Polyguard Products, Inc.
P.O. Box 755 - Ennis, TX 75120
Phone: 214-515-5000
Web Site - www.polyguard.com

©POLYGUARD PRODUCTS, INC.
MATERIAL SEPARATED FOR CLARITY

<small>The information provided is based on data and knowledge considered to be true and accurate and is offered for the users' consideration, investigation and verification, but we do not warrant the results to be obtained. Please read all data sheets, statements, recommendations or suggestions in conjunction with our conditions of sale, which apply to all goods supplied by us.</small>	NOT TO SCALE
	EFFECTIVE DATE: 07/15/2024
	SUPERCEDES: 10/01/2022