





POLYGUARD FABRIC TAPE APPLIED OVER CURED POLYGUARD LM-95 PREPARED WITH POLYGUARD 650 LT LIQUID ADHESIVE OR POLYGUARD CALIFORNIA SEALANT APPLIED AT A RATE OF 250 - 300 SF/GAL AND ONTO CLEAN, DRY FABRIC OF POLYGUARD UNDERSLAB MEMBRANE PREPARED WITH POLYGUARD 650 LT LIQUID ADHESIVE OR POLYGUARD CALIFORNIA SEALANT APPLIED AT A RATE OF 50 - 75 SF/GAL

MINIMUM 90 MILS OF POLYGUARD LM 95 APPLIED TO CLEAN, DRY AND FROST FREE CONCRETE WITH 3/4" MINIMUM CANT AROUND BASE OF PILE INTERSECTION WITH POLYGUARD UNDERSLAB FABRIC PREPARED WITH POLYGUARD 650 LT LIQUID ADHESIVE OR POLYGUARD CALIFORNIA SEALANT APPLIED AT A RATE OF 50 - 75 SF/GAL

POLYGUARD UNDERSLAB MEMBRANE FIT TIGHTLY AROUND PERIMETER OF PILE WITH FABRIC TOWARD CONCRETE POUR

US3

SECTION @ PILE TERMINATION - PROFILE 1

©POLYGUARD PRODUCTS, INC. MATERIAL SEPARATED FOR CLARITY

Polyguard Products, Inc. P.O. Box 755 - Ennis. TX 75120 Phone: 214-515-5000 Web Site - www.polyguard.com

The information provided is based on data and knowledge considered to be true and accurate and is offered for the users' consideration, investigation and verification, but we do not warrant the results to be obtained. Please read all data sheets, statements, recommendations or suggestions in conjunction with our conditions of sale, which apply to all goods supplied by us

NOT TO SCALE EFFECTIVE DATE: 07/15/2024 SUPERCEDES:

10/01/2022