



POLYGUARD 606 TAPE APPLIED TO CLEAN, DRY, FROST-FREE, RAW CONCRETE PREPARED WITH POLYGUARD 650 LT LIQUID ADHESIVE OR CALIFORNIA SEALANT APPLIED AT A RATE OF 250 - 300 SF / GAL

POLYGUARD PREFORMED US OUTSIDE CORNER BOOT ADHERED TO POLYGUARD 606 TAPE - TRIM EXCESS MATERIAL ABOVE POLYGUARD 606 TAPE

POLYGUARD UNDERSLAB TRM WITH FABRIC TOWARD CONCRETE POUR :PROVIDE TIGHT FIT AROUND CORNER / COLUMN BASE



POLYGUARD UNDERSLAB TRM 'SKIRT' ALIGNED AND ADHERED TO TOP EDGE AND VERTICAL BODY OF POLYGUARD 606 TAPE AND PREFORMED US OUTSIDE CORNER BOOT EXPOSED COMPOUND; EXTEND MINIMUM 6" ONTO HORIZONTAL UNDERSLAB TRM FIELD SHEET FABRIC AND PREFORMED US OUTSIDE CORNER BOOT EXPOSED COMPOUND



POLYGUARD LM-95 OR TRM SEALANT APPLIED TO MINIMUM 90 MILS OVER CLEAN. DRY, FROST-FREE, RAW CONCRETE; ALONG TERMINATION BAR TOP EDGE; OVER EACH FASTENER HEAD: AND EXTEND ONTO MINIMUM 1" OF POLYGUARD UNDERSLAB TRM FABRIC BELOW TERMINATION BAR PREPARED WITH POLYGUARD 650 LT LIQUID ADHESIVE OR CALIFORNIA SEALANT APPLIED AT A RATE OF 50 - 75 SF / GAL

FASTENERS SPACED MAXIMUM 8" O.C. AND MAXIMUM 2" INWARD FROM EACH END (BY OTHERS)

1/8" X 1" METAL TERMINATION BAR (BY OTHERS) ALIGNED ALONG POLYGUARD UNDERSLAB TRM 'SKIRT' AND 606 TAPE TOP EDGE

CLEAN POLYGUARD UNDERSLAB TRM FABRIC 6" TO EACH SIDE OF 'SKIRT' EDGE JUST PRIOR TO APPLYING POLYGUARD 650 LT LIQUID ADHESIVE OR CALIFORNIA SEALANT TO CLEANED AREA AT A RATE OF 50-75 SF / GAL

POLYGUARD FABRIC TAPE OVER PREPARED UNDERSLAB TRM: ROLL FABRIC TAPE WITH A HAND-HELD, HARD-SURFACE ROLLER

ISOMETRIC @ UNDERSLAB TRM - PREFORMED OUTSIDE CORNER AT COLUMN

Polyguard Products, Inc. P.O. Box 755 - Ennis, TX 75120 Phone: 214-515-5000 Web Site - www.polyguard.com

© POLYGUARD PRODUCTS, INC.

| The information provided is based on data and knowledge considered to be | L |
|--|---|
| true and accurate and is offered for the users' consideration, investigation | Ī |
| and verification, but we do not warrant the results to be obtained. Please | Ŀ |
| read all data sheets, statements, recommendations or suggestions in con- junction with our conditions of sale, which apply to all goods supplied by us. | |