





APPROVED SUBSTRATE

POLYGUARD UNDERSLAB TRM WITH FABRIC FACING TOWARD CONCRETE POUR

EXISTING CONCRETE PILE(S) TO REMAIN, CLEAN AND DRY IN PREPARATION FOR POLYGUARD UNDERSLAB TRM OVERLAY MATERIALS

POLYGUARD FABRIC TAPE APPLIED OVER CURED LM-95 OR TRM SEALANT PREPARED WITH POLYGUARD 650 LT LIQUID ADHESIVE OR CALIFORNIA SEALANT APPLIED AT A RATE OF 250 - 300 SF / GAL AND ONTO CLEAN, DRY UNDERSLAB TRM FABRIC PREPARED WITH POLYGUARD 650 LT LIQUID ADHESIVE OR CALIFORNIA SEALANT APPLIED AT A RATE OF 50 - 75 SF / GAL

POLYGUARD LM-95 OR TRM SEALANT APPLIED TO MINIMUM 90 MILS OVER CLEAN, DRY, FROST-FREE, RAW CONCRETE WITH 3/4" MINIMUM FILLET / CANT AROUND BASE OF PILE INTERSECTION WITH UNDERSLAB TRM FABRIC PREPARED WITH POLYGUARD 650 LT LIQUID ADHESIVE OR CALIFORNIA SEALANT APPLIED AT A RATE OF 50 - 75 SF / GAL

POLYGUARD UNDERSLAB TRM FIT TIGHTLY AROUND PERIMETER OF PILE WITH FABRIC TOWARD CONCRETE POUR

NOTE: WHERE PILE TOP CANNOT BE USED AS A TERMINATION AREA, INSTALL A 1" WIDE STAINLESS STEEL BAND CLAMP ALIGNED ALONG POLYGUARD FABRIC TAPE TOP EDGE

SECTION @ UNDERSLAB TRM - GRADE BEAM PILE CAP (PROFILE 1)

Polyguard Products, Inc. P.O. Box 755 - Ennis, TX 75120 Phone: 214-515-5000 Web Site - www.polyguard.com MATERIAL SEPARATED FOR CLARITY © POLYGUARD PRODUCTS, INC.

The information provided is based on data and knowledge considered to be true and accurate and is offered for the users' consideration, investigation and verification, but we do not warrant the results to be obtained. Please read all data sheets, statements, recommendations or suggestions in conjunction with our conditions of sale, which apply to all goods supplied by us

NOT TO SCALE

EFFECTIVE DATE:
12/17/2024

SUPERCEDES:
12/05/2024