



POLYGUARD 650 TRM; ROUGH-FIT AROUND PENETRATION AND OVER POLYGUARD TRM SEALANT PREPARED WITH POLYGUARD 650 LT LIQUID ADHESIVE OR CALIFORNIA SEALANT APPLIED AT A RATE OF 250 - 300 SF / GAL, OR OVER 650 WB LIQUID ADHESIVE APPLIED AT A RATE OF 350 - 400 SF / GAL

POLYGUARD TRM FLASHING OR 650 TRM TIGHT-FITTING TARGET PATCH TO CREATE A TIGHT SEAL AROUND PENETRATION BASE; EXTEND MINIMUM 6" ONTO WALL SURFACE AND MINIMUM 3" AROUND SECURED PENETRATION; APPLY OVER CLEAN AND DRY POLYGUARD SUBSTRATE MATERIALS PREPARED WITH POLYGUARD 650 LT LIQUID ADHESIVE OR CALIFORNIA SEALANT APPLIED AT A RATE OF 250 - 300 SF / GAL, OR OVER 650 WB LIQUID ADHESIVE APPLIED AT A RATE OF 350 - 400 SF / GAL

POLYGUARD 650 TRM MINIMUM 3" WIDE TIGHT-FITTING TARGET PATCH TO CREATE A TIGHT SEAL AROUND SECURED PENETRATION; APPLY OVER CLEAN AND DRY POLYGUARD SUBSTRATE MATERIALS PREPARED WITH POLYGUARD 650 LT LIQUID ADHESIVE OR CALIFORNIA SEALANT APPLIED AT A RATE OF 250 - 300 SF / GAL, OR OVER 650 WB LIQUID ADHESIVE APPLIED AT A RATE OF 350 - 400 SF / GAL

POLYGUARD LM-95, DETAIL SEALANT PW, OR TRM SEALANT APPLIED AND TOOLED TO MINIMUM 90 MILS THICK OVER CLEAN, DRY, RAW WALL CONCRETE SUBSTRATE AND ABRADED PENETRATION; EXTEND MINIMUM 6" ONTO EXISTING CONCRETE WALL SUBSTRATE AND MINIMUM 3" ONTO EXISTING ABRADED PENETRATION SUBSTRATE; WITH BOTH SUBSTRATES PREPARED USING POLYGUARD 650 LT LIQUID ADHESIVE OR CALIFORNIA SEALANT APPLIED AT A RATE OF 250 - 300 SF / GAL, OR OVER 650 WB LIQUID ADHESIVE APPLIED AT A RATE OF 350 - 400 SF / GAL

SECURED PENETRATION, CLEAN AND ABRAD E MINIMUM 3" OF BASE OF PENETRATION SIDEWALLS JUST PRIOR TO POLYGUARD 650 TRM SYSTEM APPLICATION

POLYGUARD LM-95, DETAIL SEALANT PW, OR TRM SEALANT BARRIER APPLIED AND TOOLED TO MINIMUM 90 MILS OVER ALL 650 TRM TARGET PATCH TERMINAL EDGES AS EDGE SEAL

BACKER ROD (BY OTHERS)

POLYGUARD POLYFLOW 15 OR 15P SHEET-MOLDED DRAINAGE AND PROTECTION BOARD WITH FABRIC FACING BACKFILL / SOIL

WPT14

SECTION @ 650 TRM - WALL PENETRATION

GENERAL NOTE: IF ADHESIVE IS REQUIRED FOR SEAMS OR END LAPS, DO NOT USE POLYGUARD 650 WB LIQUID ADHESIVE.

MATERIAL SEPARATED FOR CLARITY
© POLYGUARD PRODUCTS, INC.

<p>The information provided is based on data and knowledge considered to be true and accurate and is offered for the users' consideration, investigation and verification, but we do not warrant the results to be obtained. Please read all data sheets, statements, recommendations or suggestions in conjunction with our conditions of sale, which apply to all goods supplied by us.</p>	NOT TO SCALE
	EFFECTIVE DATE: 12/17/2024
	SUPERCEDES: 12/10/2024