





CONCRETE OR CMU PLANTER (BY OTHERS)

SOIL (BY OTHERS)

POLYGUARD POLYFLOW 15/15P VERTICAL DRAINBOARD WITH FABRIC FACING TOWARDS SOIL

POLYGUARD 650 TRM APPLIED TO SUBSTRATE PREPARED WITH POLYGUARD 650 LT LIQUID ADHESIVE OR POLYGUARD CALIFORNIA SEALANT AT A RATE OF 250 - 300 SF / GAL, OR OVER POLYGUARD 650 WB LIQUID ADHESIVE AT A RATE OF 350 - 400 SF / GAL

12" STRIP OF POLYGUARD TRM FLASHING APPLIED TO SUBSTRATE PREPARED WITH POLYGUARD 650 LT LIQUID ADHESIVE OR CALIFORNIA SEALANT APPLIED AT A RATE OF 250 - 300 SF / GAL, OR OVER 650 WB LIQUID ADHESIVE APPLIED AT A RATE OF 350 - 400 SF / GAL

POLYGUARD LM-95, DETAIL SEALANT PW, OR TRM SEALANT APPLIED AND TOOLED TO MINIMUM 3/4" CANT / FILLET OVER RAW CONCRETE OR CMU ON ALL INSIDE CORNERS VERTICALLY AND HORIZONTALLY; ALLOW TO CURE FOR MINIMUM 2 HOURS PRIOR TO OVERLAY SHEET WATERPROOOFING MEMBRANE APPLICATION

NOTE: BUILD CMU WALLS WITH JOINTS ON WATERPROOFING SIDE, STRUCK FLUSH WITH CMU FACE. PARGE COAT CMU FACE ON WATERPROOFING SIDE, OR PREPARE WATERPROOFING SIDE SUBSTRATE SURFACE WITH POLYGUARD STRETCH FLEX WATERPROOFING MEMBRANE APPLIED TO MINIMUM CONTINUOUS 60 MILS

POLYGUARD POLYFLOW 18 HORIZONTAL DRAINBOARD WITH WOVEN FILTER FABRIC FACING TOWARDS SOIL



\SECTION @ 650 TRM - POURED CONCRETE OR CMU PLANTER

Polyguard Products, Inc. P.O. Box 755 - Ennis, TX 75120 Phone: 214-515-5000 Web Site - www.polyguard.com

<u>GENERAL NOTE:</u> IF ADHESIVE IS REQUIRED FOR SEAMS OR END LAPS, DO NOT USE POLYGUARD 650 WB LIQUID ADHESIVE.

MATERIAL SEPARATED FOR CLARITY

© POLYGUARD PRODUCTS. INC.

The information provided is based on data and knowledge considered to be true and accurate and is offered for the users' consideration, investigation and verification, but we do not warrant the results to be obtained. Please read all data sheets, stalements, recommendations or suggestions in conjunction with our conditions of siale, which apply to all goods supplied by us

NOT TO SCALE

EFFECTIVE DATE:
12/17/2024

SUPERCEDES:
12/10/2024