

HPD UNIQUE IDENTIFIER: 24770

CLASSIFICATION: 07 27 13 Modified Bituminous Sheet Air Barriers

PRODUCT DESCRIPTION: Airlok® Sheet 400 NP Air and Moisture Barrier is a non-permeable sheet membrane, available in various sizes, designed for air and moisture protection in both field and flashing applications. Airlok® Sheet 400 NP, when applied to a structural substrate, will give excellent resistance to air leakage and vapor diffusion. Strengths – Traditional 40-mil rubberized-asphalt sheet for field membranes and works well as window and through wall flashings. Airlok® Sheet 400 NP can be applied at temperatures of 25°F (-4°C) and rising. Limitations – 60-day UV exposure, maximum in-service temperature of 160°F, and limited NFPA 285 assembly. Uses – Field membrane, window flashing and through wall flashing for assemblies such as brick facades.

Section 1: Summary

Basic Method / Product Threshold

CONTENT INVENTORY

Inventory Reporting Format	Threshold level	Residuals/Impurities	<i>All Substances Above the Threshold Indicated Are:</i>
<input type="radio"/> Nested Materials Method	<input checked="" type="radio"/> 100 ppm	<input checked="" type="radio"/> Considered	Characterized <input type="radio"/> Yes Ex/SC <input checked="" type="radio"/> Yes <input type="radio"/> No
<input checked="" type="radio"/> Basic Method	<input type="radio"/> 1,000 ppm	<input type="radio"/> Partially Considered	<i>% weight and role provided for all substances.</i>
Threshold Disclosed Per	<input type="radio"/> Per GHS SDS	<input type="radio"/> Not Considered	Screened <input type="radio"/> Yes Ex/SC <input checked="" type="radio"/> Yes <input type="radio"/> No
<input type="radio"/> Material	<input type="radio"/> Other	Explanation(s) provided for Residuals/Impurities?	<i>All substances screened using Priority Hazard Lists with results disclosed.</i>
<input checked="" type="radio"/> Product		<input checked="" type="radio"/> Yes <input type="radio"/> No	Identified <input type="radio"/> Yes Ex/SC <input type="radio"/> Yes <input checked="" type="radio"/> No
			<i>One or more substances not disclosed by Name (Specific or Generic) and Identifier and/ or one or more Special Condition did not follow guidance.</i>

CONTENT IN DESCENDING ORDER OF QUANTITY

Summary of product contents and results from screening individual chemical substances against HPD Priority Hazard Lists and the GreenScreen for Safer Chemicals®. The HPD does not assess whether using or handling this product will expose individuals to its chemical substances or any health risk. Refer to Section 2 for further details.

MATERIAL | SUBSTANCE | RESIDUAL OR IMPURITY
GREENSCREEN SCORE | HAZARD TYPE
AIRLOK® SHEET 400 NP [ASPHALT LT-1 | CAN LIMESTONE LT-UNK
POLYETHYLENE (PRIMARY CASRN IS 9002-88-4) LT-UNK
UNDISCLOSED LT-1 | CAN | PBT | MUL UNDISCLOSED LT-1 | CAN
STYRENE BUTADIENE RUBBER (BENZENE, ETHENYL-, POLYMER WITH 1,3-BUTADIENE) LT-UNK BENZENE, ETHENYL-, POLYMER WITH 2-METHYL-1,3-BUTADIENE LT-UNK UNDISCLOSED LT-P1 | AQU
| END | MAM | MUL | PHY UNDISCLOSED LT-1 | PBT | CAN
UNDISCLOSED LT-1 | CAN]

Number of Greenscreen BM-4/BM3 contents ... 0

Contents highest concern GreenScreen Benchmark or List translator Score ... LT-1
 Nanomaterial ... No

INVENTORY AND SCREENING NOTES:

Reviewed raw material SDS for listing of impurities and residuals.

VOLATILE ORGANIC COMPOUND (VOC) CONTENT

VOC Content data is not applicable for this product category.

CERTIFICATIONS AND COMPLIANCE See Section 3 for additional listings.

VOC emissions: N/A

CONSISTENCY WITH OTHER PROGRAMS

No pre-checks completed or disclosed.

Third Party Verified?

- Yes
- No

PREPARER: Self-Prepared

VERIFIER:
VERIFICATION #:

SCREENING DATE: 2021-05-12

PUBLISHED DATE: 2021-05-13

EXPIRY DATE: 2024-05-12

Section 2: Content in Descending Order of Quantity

This section lists contents in a product based on specific threshold(s) and reports detailed health information including hazards. This HPD uses the inventory method indicated above, which is one of three possible methods:

- Basic Inventory method with Product-level threshold.
- Nested Material Inventory method with Product-level threshold
- Nested Material Inventory method with individual Material-level thresholds

Definitions and requirements for the three inventory methods and requirements for each data field can be found in the HPD Open Standard version 2.2, available on the HPDC website at: www.hpdc-collaborative.org/hpd-2-2-standard

AIRLOK® SHEET 400 NP

PRODUCT THRESHOLD: 100 ppm

RESIDUALS AND IMPURITIES CONSIDERED: Yes

RESIDUALS AND IMPURITIES NOTES: Reviewed raw material SDS for listing of impurities and residuals.

OTHER PRODUCT NOTES: No additional notes

ASPHALT

ID: 8052-42-4

HAZARD SCREENING METHOD: **Pharos Chemical and Materials Library** HAZARD SCREENING DATE: **2021-05-12 6:18:34**

#: **50.0000 - 60.0000** GS: **LT-1** RC: **None** NANO: **No** SUBSTANCE ROLE: **Binder**

HAZARD TYPE	AGENCY AND LIST TITLES	WARNINGS
CAN	US CDC - Occupational Carcinogens	Occupational Carcinogen
CAN	MAK	Carcinogen Group 3B - Evidence of carcinogenic effects but not sufficient for classification
CAN	IARC	Group 2B - Possibly carcinogenic to humans - inhaled from occupational sources
CAN	CA EPA - Prop 65	Carcinogen
CAN	IARC	Group 2b - Possibly carcinogenic to humans

SUBSTANCE NOTES:

LIMESTONE

ID: 1317-65-3

HAZARD SCREENING METHOD: **Pharos Chemical and Materials Library** HAZARD SCREENING DATE: **2021-05-12 6:18:35**

#: **10.0000 - 20.0000** GS: **LT-UNK** RC: **None** NANO: **No** SUBSTANCE ROLE: **Filler**

HAZARD TYPE	AGENCY AND LIST TITLES	WARNINGS
None found		No warnings found on HPD Priority Hazard Lists

SUBSTANCE NOTES:

POLYETHYLENE (PRIMARY CASRN IS 9002-88-4)

ID: 934176-14-4

HAZARD SCREENING METHOD: **Pharos Chemical and Materials Library** HAZARD SCREENING DATE: **2021-05-12 6:18:35**

#: **5.0000 - 9.0000** GS: **LT-UNK** RC: **None** NANO: **No** SUBSTANCE ROLE: **Structure component**

HAZARD TYPE	AGENCY AND LIST TITLES	WARNINGS
None found		No warnings found on HPD Priority Hazard Lists
SUBSTANCE NOTES: Polyethylene film		

UNDISCLOSED

ID: **Undisclosed**

HAZARD SCREENING METHOD: Pharos Chemical and Materials Library		HAZARD SCREENING DATE: 2021-05-12 6:18:36		
%: Impurity/Residual	GS: LT-1	RC: None	NANO: No	SUBSTANCE ROLE: Impurity/Residual
HAZARD TYPE	AGENCY AND LIST TITLES	WARNINGS		
CAN	EU - GHS (H-Statements)	H350 - May cause cancer		
CAN	EU - REACH Annex XVII CMRs	Carcinogen Category 2 - Substances which should be regarded as if they are Carcinogenic to man		
CAN	EU - Annex VI CMRs	Carcinogen Category 1B - Presumed Carcinogen based on animal evidence		
PBT	EC - CEPA DSL	Persistent, Bioaccumulative and inherently Toxic (PBiTE) to the Environment (based on aquatic organisms)		
PBT	EC - CEPA DSL	Persistent, Bioaccumulative and inherently Toxic (PBiTH) to humans		
MUL	ChemSec - SIN List	CMR - Carcinogen, Mutagen &/or Reproductive Toxicant		
MUL	German FEA - Substances Hazardous to Waters	Class 3 - Severe Hazard to Waters		
CAN	GHS - Australia	H350 - May cause cancer		

SUBSTANCE NOTES: Natural occurring component of asphalt.

UNDISCLOSED

ID: **Undisclosed**

HAZARD SCREENING METHOD: Pharos Chemical and Materials Library		HAZARD SCREENING DATE: 2021-05-12 6:18:36		
%: Impurity/Residual	GS: LT-1	RC: None	NANO: No	SUBSTANCE ROLE: Impurity/Residual
HAZARD TYPE	AGENCY AND LIST TITLES	WARNINGS		
CAN	US CDC - Occupational Carcinogens	Occupational Carcinogen		
CAN	MAK	Carcinogen Group 3B - Evidence of carcinogenic effects but not sufficient for classification		
CAN	IARC	Group 2B - Possibly carcinogenic to humans - inhaled from occupational sources		
CAN	CA EPA - Prop 65	Carcinogen		
CAN	IARC	Group 2b - Possibly carcinogenic to humans		

SUBSTANCE NOTES: Natural occurring component of asphalt.

STYRENE BUTADIENE RUBBER (BENZENE, ETHENYL-, POLYMER WITH 1,3-BUTADIENE)

ID: **9003-55-8**

HAZARD SCREENING METHOD: Pharos Chemical and Materials Library		HAZARD SCREENING DATE: 2021-05-12 6:18:37	
#: 2.0000 - 7.0000	GS: LT-UNK	RC: None	NANO: No SUBSTANCE ROLE: Polymer species
HAZARD TYPE	AGENCY AND LIST TITLES	WARNINGS	
None found		No warnings found on HPD Priority Hazard Lists	
SUBSTANCE NOTES:			

BENZENE, ETHENYL-, POLYMER WITH 2-METHYL-1,3-BUTADIENE ID: **25038-32-8**

HAZARD SCREENING METHOD: Pharos Chemical and Materials Library		HAZARD SCREENING DATE: 2021-05-12 6:18:37	
#: 2.0000 - 6.0000	GS: LT-UNK	RC: None	NANO: No SUBSTANCE ROLE: Polymer species
HAZARD TYPE	AGENCY AND LIST TITLES	WARNINGS	
None found		No warnings found on HPD Priority Hazard Lists	
SUBSTANCE NOTES:			

UNDISCLOSED ID: **Undisclosed**

HAZARD SCREENING METHOD: Pharos Chemical and Materials Library		HAZARD SCREENING DATE: 2021-05-12 6:18:37	
#: Impurity/Residual	GS: LT-P1	RC: None	NANO: No SUBSTANCE ROLE: Impurity/Residual
HAZARD TYPE	AGENCY AND LIST TITLES	WARNINGS	
AQU	EU - GHS (H-Statements)	H400 - Very toxic to aquatic life	
END	TEDX - Potential Endocrine Disruptors	Potential Endocrine Disruptor	
MAM	EU - GHS (H-Statements)	H330 - Fatal if inhaled	
MUL	German FEA - Substances Hazardous to Waters	Class 2 - Hazard to Waters	
MAM	US EPA - EPCRA Extremely Hazardous Substances	Extremely Hazardous Substances	
PHY	EU - GHS (H-Statements)	H220 - Extremely flammable gas	
SUBSTANCE NOTES: Natural occurring component of asphalt.			

UNDISCLOSED ID: **Undisclosed**

HAZARD SCREENING METHOD: Pharos Chemical and Materials Library		HAZARD SCREENING DATE: 2021-05-12 6:18:38	
#: Impurity/Residual	GS: LT-1	RC: None	NANO: No SUBSTANCE ROLE: Impurity/Residual

HAZARD TYPE	AGENCY AND LIST TITLES	WARNINGS
PBT	OSPAR - Priority PBTs & EDs & equivalent concern	PBT - Chemical for Priority Action
CAN	MAK	Carcinogen Group 1 - Substances that cause cancer in man
CAN	US NIH - Report on Carcinogens	Reasonably Anticipated to be Human Carcinogen
PBT	WA DoE - PBT	PBT
PBT	US EPA - Toxics Release Inventory PBTs	PBT

SUBSTANCE NOTES: Natural occurring component of asphalt.

UNDISCLOSED

ID: **Undisclosed**

HAZARD SCREENING METHOD: **Pharos Chemical and Materials Library** HAZARD SCREENING DATE: **2021-05-12 6:18:39**

%: **Impurity/Residual** GS: **LT-1** RC: **None** NANO: **No** SUBSTANCE ROLE: **Impurity/Residual**

HAZARD TYPE	AGENCY AND LIST TITLES	WARNINGS
CAN	US CDC - Occupational Carcinogens	Occupational Carcinogen
CAN	CA EPA - Prop 65	Carcinogen - specific to chemical form or exposure route
CAN	US NIH - Report on Carcinogens	Known to be Human Carcinogen (respirable size - occupational setting)
CAN	MAK	Carcinogen Group 1 - Substances that cause cancer in man
CAN	IARC	Group 1 - Agent is carcinogenic to humans - inhaled from occupational sources
CAN	IARC	Group 1 - Agent is Carcinogenic to humans
CAN	GHS - Australia	H350i - May cause cancer by inhalation
CAN	GHS - New Zealand	6.7A - Known or presumed human carcinogens
CAN	GHS - Japan	Carcinogenicity - Category 1A [H350]

SUBSTANCE NOTES: Natural occurring component of Limestone.

Section 3: Certifications and Compliance

This section lists applicable certification and standards compliance information for VOC emissions and VOC content. Other types of health or environmental performance testing or certifications completed for the product may be provided.

VOC EMISSIONS

N/A

CERTIFYING PARTY: Self-declared

ISSUE DATE: 2021-04-

EXPIRY DATE:

CERTIFIER OR LAB: None

APPLICABLE FACILITIES: All

07

CERTIFICATE URL:

CERTIFICATION AND COMPLIANCE NOTES: VOC content data is not applicable for this product category.

Section 4: Accessories

This section lists related products or materials that the manufacturer requires or recommends for installation (such as adhesives or fasteners), maintenance, cleaning, or operations. For information relating to the contents of these related products, refer to their applicable Health Product Declarations, if available.

DETAIL SEALANT PW™

HPD URL: <https://hpdrepository.hpd-collaborative.org/Pages/Results.aspx#k=polyguard>

CONDITION WHEN RECOMMENDED OR REQUIRED AND/OR OTHER NOTES:

Detail Sealant PW™ is used to address the critical areas of terminations, transitions and penetrations.

650 LT LIQUID ADHESIVE

HPD URL: <https://hpdrepository.hpd-collaborative.org/Pages/Results.aspx#k=polyguard>

CONDITION WHEN RECOMMENDED OR REQUIRED AND/OR OTHER NOTES:

All substrates must be prepared prior to application of membrane. Apply to a cleaned, dry, dust free, and frost free surface. Apply by roller or brush. Apply Polyguard® 650 LT Liquid Adhesive per manufacturer's instructions. Allow to cure per manufacturer's directions.

CALIFORNIA SEALANT

HPD URL: <https://hpdrepository.hpd-collaborative.org/Pages/Results.aspx#k=polyguard>

CONDITION WHEN RECOMMENDED OR REQUIRED AND/OR OTHER NOTES:

All substrates must be prepared prior to application of membrane. Apply to a cleaned, dry, dust free, and frost free surface. Apply by roller or brush. Apply Polyguard® California Sealant per manufacturer's instructions. Allow to cure per manufacturer's directions.

650 WB LIQUID ADHESIVE

HPD URL: <https://hpdrepository.hpd-collaborative.org/Pages/Results.aspx#k=polyguard>

CONDITION WHEN RECOMMENDED OR REQUIRED AND/OR OTHER NOTES:

All substrates must be prepared prior to application of membrane. Apply to a cleaned, dry, dust free, and frost free surface. Apply by roller or brush. Apply Polyguard® 650 WB Liquid Adhesive per manufacturer's instructions. Allow to cure per manufacturer's directions.

Section 5: General Notes

No additional general notes for this product.

MANUFACTURER INFORMATION

MANUFACTURER: Polyguard Products
ADDRESS: 4101 S I 45
Ennis Texas 75119, United States
WEBSITE: www.Polyguard.com

CONTACT NAME: Chris Rogalski
TITLE: Quality Mgr.
PHONE: 214-515-5000
EMAIL: Polyguard@polyguard.com

The listed contact is responsible for the validity of this HPD and attests that it is accurate and complete to the best of his or her knowledge.

KEY

Hazard Types

AQU Aquatic toxicity	LAN Land toxicity	PHY Physical hazard (flammable or reactive)
CAN Cancer	MAM Mammalian/systemic/organ toxicity	REP Reproductive
DEV Developmental toxicity	MUL Multiple	RES Respiratory sensitization
END Endocrine activity	NEU Neurotoxicity	SKI Skin sensitization/irritation/corrosivity
EYE Eye irritation/corrosivity	NF Not found on Priority Hazard Lists	UNK Unknown
GEN Gene mutation	OZO Ozone depletion	
GLO Global warming	PBT Persistent, bioaccumulative, and toxic	

GreenScreen (GS)

BM-4 Benchmark 4 (prefer-safer chemical)	LT-1 List Translator 1 (Likely Benchmark-1)
BM-3 Benchmark 3 (use but still opportunity for improvement)	LT-UNK List Translator Benchmark Unknown (the chemical is present on at least one GreenScreen Specified List, but the information contained within the list did not result in a clear mapping to a LT-1 or LTP1 score.)
BM-2 Benchmark 2 (use but search for safer substitutes)	NoGS No GreenScreen.
BM-1 Benchmark 1 (avoid - chemical of high concern)	
BM-U Benchmark Unspecified (due to insufficient data)	
LT-P1 List Translator Possible 1 (Possible Benchmark-1)	

Recycled Types

PreC Pre-consumer recycled content
PostC Post-consumer recycled content
UNK Inclusion of recycled content is unknown
None Does not include recycled content

Other Terms:

GHS SDS Globally Harmonized System of Classification and Labeling of Chemicals Safety Data Sheet

Inventory Methods:

Nested Method / Material Threshold Substances listed within each material per threshold indicated per material
Nested Method / Product Threshold Substances listed within each material per threshold indicated per product
Basic Method / Product Threshold Substances listed individually per threshold indicated per product

Nano Composed of nano scale particles or nanotechnology
Third Party Verified Verification by independent certifier approved by HPDC
Preparer Third party preparer, if not self-prepared by manufacturer
Applicable facilities Manufacturing sites to which testing applies

The Health Product Declaration (HPD) Open Standard provides for the disclosure of product contents and potential associated human and environmental health hazards. Hazard associations are based on the HPD Priority Hazard Lists, the GreenScreen List Translator™, and when available, full GreenScreen® assessments. The HPD Open Standard v2.1 is not:

- a method for the assessment of exposure or risk associated with product handling or use,
- a method for assessing potential health impacts of: (i) substances used or created during the manufacturing process or (ii) substances created after the product is delivered for end use.

Information about life cycle, exposure and/or risk assessments performed on the product may be reported by the manufacturer in appropriate Notes sections, and/or, where applicable, in the Certifications section.

The HPD Open Standard was created and is supported by the Health Product Declaration Collaborative (the HPD Collaborative), a customer-led organization composed of stakeholders throughout the building industry that is committed to the continuous improvement of building products through transparency, openness, and innovation throughout the product supply chain.

The product manufacturer and any applicable independent verifier are solely responsible for the accuracy of statements and claims made in this HPD and for compliance with the HPD standard noted.