

## 650 TRM

### WATERPROOFING SYSTEM: BELOW-GRADE SHEET MEMBRANE

#### 650 TRM

650 TRM is a non-structural barrier which when properly constructed as part of the building envelope, it blocks both termites and water. It is formulated for low temperature application down to 30°F (-1°C) on concrete and down to 40°F (5°C) on ICF. 650 TRM can also be used horizontally on tunnel roofs, plaza decks et. al., when used in combination with Polyflow® drainage. Horizontal uses over conditioned and/or habitable space for decks and balconies must have Polyguard's approval prior to starting work. All horizontal surfaces to be waterproofed must have positive slope and proper drainage. If deck is not sloped, contact Polyguard Products for specific details.

Check	Part Number	Unit Size	Units/pallet	Wt/unit
650 TRM	TERMFOUND36	36" x 66.7'roll	30 rolls/pallet	75#/roll
<b>650 TRM System Components (where applicable):</b>	<b>Part Number</b>	<b>Unit Size</b>	<b>Units/pallet</b>	<b>Wt/unit</b>
<i>Choose product relative to specific application.</i>				
650 LT Liquid Adhesive • 5 gal. pail	650-5 LIQ ADH 5 GA	5-gallon pail	36 pails/pallet	45#/pail
650 LT Liquid Adhesive • 4 – 1 gal. pails	650-5 LIQ ADH 1 GA	4 – 1 gal pails/ctn	54 ctns/pallet	31#/ctn
650 WB Liquid Adhesive • 5 gal. pail (for ICF)	PG.650.WB.5	5-gallon pail	36 pails/pallet	45#/pail
650 WB Liquid Adhesive • 4 – 1 gal. pails (for ICF)	PG.650.WB.1.CTN	4 – 1 gal pails/ctn	48 ctns/pallet	40#/ctn
California Sealant	CALSEAL5	5-gallon pail	36 pails/pallet	45#/pail
LM-95	LM952	2-gallon pail	80 pails/pallet	20#/pail
Detail Sealant PW™ . 20 oz. sausage	DETAIL SEALANT PW – SAU 20 OZ	20 sausages/ctn	45 ctns/pallet	45#/ctn
Detail Sealant PW™ . 3 gal. pail	DETAIL SEALANT PW – 3 GAL	3-gallon pail	36 pails/pallet	37#/pail
<i>* Detail Sealant PW™ required in certain details – contact Polyguard Products.</i>				
TRM Sealant • 4 – 1 qt. cans	TERMSEAL Q X 4	4 – 1 qt cans/ctn	40 ctns/pallet	9#/ctn
TRM Sealant • 4 – 1 gal. cans	TERMSEAL GALLON X 4	4 – 1 gal cans/ctn	36 ctns/pallet	36#/ctn
<b>Possible Accessories:</b>	<b>Part Number</b>	<b>Unit Size</b>	<b>Units/pallet</b>	<b>Wt/unit</b>
LM-85 SSL • 5 gal. pail	LM85-5 SSL	5-gallon pail	36 pails/pallet	48#/pail
LM-85 SSL • 2 gal. pail	LM85-2 SSL	2-gallon pail	80 pails/pallet	20#/pail
<b>Possible Drainage Accessories:</b>	<b>Part Number</b>	<b>Unit Size</b>	<b>Units/pallet</b>	<b>Wt/unit</b>
Polyflow® BD (For Balcony Applications Only)	POLYFLOWBD	4' x 50' roll	9 rolls/pallet	38#/roll
Polyflow® 15	POLYFLOW15	4' x 50' roll	7 rolls/pallet	39#/roll
Polyflow® 15P	POLYFLOW15P	4' x 50' roll	7 rolls/pallet	40.5#/roll
Polyflow® 18	POLYFLOW18	4' x 50' roll	7 rolls/pallet	50#/roll
Totalflow™	TOTAL FLOW	24" x 50' roll	12 rolls/pallet	30#/roll
Totalflow™ End Outlet (4")	OUTLET4-UNIV	N/A	N/A	
Totalflow™ Tee Outlet (4")	TEE4-UNIV	N/A	N/A	N/A

Weights listed are estimat

**DISCLAIMER:** The information contained in this document is based on data and knowledge considered to be true and accurate at time of printing and is offered for the users' consideration, investigation and verification. Polyguard Products, Inc. cannot be held liable for errors made as a result of information herein. Changes and modifications can be made to this document without prior notice. No statement, recommendation or suggestion is intended for use which would infringe on patents or copyrights held by Polyguard Products, Inc.