

## 650 MEMBRANE

### WATERPROOFING SYSTEM: BELOW-GRADE SHEET MEMBRANE

#### Polyguard 650 Membrane

The primary use for 650 Membrane is sheet-applied below-grade wall waterproofing for ambient and substrate surface temperatures of 40°F (5°C) and rising. It can also be used horizontally on tunnel roofs, plaza decks, parking garages, and related applications where waterproofing is critical. Polyguard 650 Membrane may also be used on wood, concrete masonry (CMU) structures, and Insulated Concrete Forms (ICF). For balcony applications over conditioned space, 650 Membrane shall be used as part of Polyguard's Dual Core System. See the 650 Membrane Balcony Detail for assembly requirements. All other horizontal uses over conditioned and/or habitable space must have Polyguard's approval prior to starting work. All horizontal surfaces to be waterproofed must have positive slope and proper drainage. If the deck is not sloped, contact Polyguard Products for specific details.

Check	Part Number	Unit Size	Units/pallet	Wt/unit
Polyguard 650 Membrane	650L36	36" x 66.7' roll	30 rolls/pallet	75#/roll
	650L48	48" x 50' roll	25 rolls/pallet	75#/roll
<b>650 Membrane System Components (where applicable):</b>	<b>Part Number</b>	<b>Unit Size</b>	<b>Units/pallet</b>	<b>Wt/unit</b>
Detail Tape	650L12	4 – 12" x 50' rolls/ctn	25 ctns/pallet	75#/ctn
<i>Choose product relative to specific application.</i>				
650 LT Liquid Adhesive • 5 gal. pail	650-5 LIQ ADH 5 GA	5-gallon pail	36 pails/pallet	45#/pail
650 LT Liquid Adhesive • 4 – 1 gal. pails	650-5 LIQ ADH 1 GA	4 – 1 gal pails/ctn	54 ctns/pallet	31#/ctn
650 WB Liquid Adhesive • 5 gal. pail	PG.650.WB.5	5-gallon pail	36 pails/pallet	45#/pail
California Sealant	CALSEAL5	5-gallon pail	36 pails/pallet	45#/pail
LM-95	LM952	2-gallon pail	80 pails/pallet	20#/pail
* Detail Sealant PW™ . 20 oz. sausage	DETAIL SEALANT PW – SAU 20 OZ	20 sausages/ctn	45 ctns/pallet	45#/ctn
<i>* Detail Sealant PW™ required in certain details – contact Polyguard Products.</i>				
<b>Possible Accessories:</b>	<b>Part Number</b>	<b>Unit Size</b>	<b>Units/pallet</b>	<b>Wt/unit</b>
LM-85 SSL • 5 gal. pail	LM85-5 SSL	5-gallon pail	36 pails/pallet	48#/pail
LM-85 SSL • 2 gal. pail	LM85-2 SSL	2-gallon pail	80 pails/pallet	20#/pail
<b>Possible Drainage Accessories:</b>	<b>Part Number</b>	<b>Unit Size</b>	<b>Units/pallet</b>	<b>Wt/unit</b>
Polyflow® BD (For Balcony Applications Only)	POLYFLOWBD	4' x 50' roll	9 rolls/pallet	38#/roll
Polyflow® 15	POLYFLOW15	4' x 50' roll	7 rolls/pallet	39#/roll
Polyflow® 15P	POLYFLOW15P	4' x 50' roll	7 rolls/pallet	40.5#/roll
Polyflow® 18	POLYFLOW18	4' x 50' roll	7 rolls/pallet	50#/roll
Totalflow™	TOTAL FLOW	24" x 50' roll	12 rolls/pallet	30#/roll
Totalflow™ End Outlet (4")	OUTLET4-UNIV	N/A	N/A	
Totalflow™ Tee Outlet (4")	TEE4-UNIV	N/A	N/A	N/A

**Weights listed are estimates**

**DISCLAIMER:** The information contained in this document is based on data and knowledge considered to be true and accurate at time of printing and is offered for the users' consideration, investigation and verification. Polyguard Products, Inc. cannot be held liable for errors made as a result of information herein. Changes and modifications can be made to this document without prior notice. No statement, recommendation or suggestion is intended for use which would infringe on patents or copyrights held by Polyguard Products, Inc.