

650 MEMBRANE

WATERPROOFING SYSTEM: BELOW-GRADE SHEET MEMBRANE

Polyguard 650 Membrane

The primary use for 650 Membrane is sheet-applied below-grade wall waterproofing for ambient and substrate surface temperatures of 40° F (5° C) and rising. It can also be used horizontally on tunnel roofs, plaza decks et. al., when used in combination with Polyflow® drainage. Horizontal uses over conditioned and/or habitable space for decks and balconies must have Polyguard's approval prior to starting work. All horizontal surfaces to be waterproofed must have positive slope and proper drainage. If deck is not sloped, contact Polyguard Products for specific details.

| Check | Part Number | Unit Size | Units/pallet | Wt/unit |
|---|-------------------------------|-------------------------|-----------------|------------|
| Polyguard 650 Membrane | 650L36 | 36" x 66.7'roll | 30 rolls/pallet | 75#/roll |
| | 650L48 | 48" x 50'roll | 25 rolls/pallet | 75#/roll |
| 650 Membrane System Components (where applicable): | Part Number | Unit Size | Units/pallet | Wt/unit |
| Detail Tape | 650L12 | 4 – 12" x 50' rolls/ctn | 25 ctns/pallet | 75#/ctn |
| Choose product relative to specific application. | | | | |
| 650 LT Liquid Adhesive • 5 gal. pail | 650-5 LIQ ADH 5 GA | 5-gallon pail | 36 pails/pallet | 45#/pail |
| 650 LT Liquid Adhesive • 4 – 1 gal. pails | 650-5 LIQ ADH 1 GA | 4 – 1 gal pails/ctn | 54 ctns/pallet | 31#/ctn |
| 650 WB Liquid Adhesive • 5 gal. pail | PG.650.WB.5 | 5-gallon pail | 36 pails/pallet | 45#/pail |
| California Sealant | CALSEAL5 | 5-gallon pail | 36 pails/pallet | 45#/pail |
| LM-95 | LM952 | 2-gallon pail | 80 pails/pallet | 20#/pail |
| * Detail Sealant PW™ - 20 oz. sausage | DETAIL SEALANT PW - SAU 20 OZ | 20 sausages/ctn | 45 ctns/pallet | 45#/ctn |
| * Detail Sealant PW™ required in certain details – contact Poly | guard Products. | - | | • |
| Possible Accessories: | Part Number | Unit Size | Units/pallet | Wt/unit |
| LM-85 SSL • 5 gal. pail | LM85-5 SSL | 5-gallon pail | 36 pails/pallet | 48#/pail |
| LM-85 SSL • 2 gal. pail | LM85-2 SSL | 2-gallon pail | 80 pails/pallet | 20#/pail |
| Possible Drainage Accessories: | Part Number | Unit Size | Units/pallet | Wt/unit |
| Polyflow® BD (For Balcony Applications Only) | POLYFLOWBD | 4' x 50' roll | 9 rolls/pallet | 38#/roll |
| Polyflow® 15 | POLYFLOW15 | 4' x 50' roll | 7 rolls/pallet | 39#/roll |
| Polyflow® 15P | POLYFLOW15P | 4' x 50' roll | 7 rolls/pallet | 40.5#/roll |
| Polyflow® 18 | POLYFLOW18 | 4' x 50' roll | 7 rolls/pallet | 50#/roll |
| Totalflow™ | TOTAL FLOW | 24" x 50' roll | 12 rolls/pallet | 30#/roll |
| Totalflow™ End Outlet (4") | OUTLET4-UNIV | N/A | N/A | |
| Totalflow™ Tee Outlet (4") | TEE4-UNIV | N/A | N/A | N/A |

Weights listed are estimates

DISCLAIMER: The information contained in this document is based on data and knowledge considered to be true and accurate at time of printing and is offered for the users' consideration, investigation and verification. Polyguard Products, Inc. cannot be held liable for errors made as a result of information herein. Changes and modifications can be made to this document without prior notice. No statement, recommendation or suggestion is intended for use which would infringe on patents or copyrights held by Polyguard Products, Inc.

