

DECKGUARD® HT

WATERPROOFING SYSTEM: SPECIALTY SHEET MEMBRANE

Polyguard Deckguard® HT

Deckguard® HT is designed as a high temperature underlayment (260° F) for under shingles, tile, or standing seam metal roofing.

Check	Part Number	Unit Size	Units/pallet	Wt/unit
	Polyguard Deckguard HT® Membrane	BALCONY GUARD 48	48" x 50'roll	25 rolls/pallet 75#/roll
<i>* Accessories may be required – contact Polyguard Products for assistance with your application requirements.</i>				
	Possible Accessories (where applicable):	Part Number	Unit Size	Units/pallet Wt/unit
	* 650 LT Liquid Adhesive • 5 gal. pail	650-5 LIQ ADH 5 GA	5-gallon pail	36 pails/pallet 45#/pail
	* 650 LT Liquid Adhesive • 4 – 1 gal. pails	650-5 LIQ ADH 1 GA	4 – 1 gal pails/ctn	54 ctns/pallet 31#/ctn
	* 650 WB Liquid Adhesive • 5 gal. pail	PG.650.WB.5	5-gallon pail	36 pails/pallet 45#/pail
	* California Sealant	CALSEAL5	5-gallon pail	36 pails/pallet 45#/pail
	* Detail Sealant PW™ • 20 oz. sausage	DETAIL SEALANT PW – SAU 20 OZ	20 sausages/ctn	45 ctns/pallet 45#/ctn
	* Detail Sealant PW™ • 3 gal. pail	DETAIL SEALANT PW – 3 GAL	3-gallon pail	36 pails/pallet 37#/pail

Weights listed are estimates

DISCLAIMER: The information contained in this document is based on data and knowledge considered to be true and accurate at time of printing and is offered for the users' consideration, investigation and verification. Polyguard Products, Inc. cannot be held liable for errors made as a result of information herein. Changes and modifications can be made to this document without prior notice. No statement, recommendation or suggestion is intended for use which would infringe on patents or copyrights held by Polyguard Products, Inc.