

# PRODUCT DATA SHEET



## FABRIC TAPE

Fabric Adhesive Tape

### MANUFACTURER

Polyguard Products, Inc.  
Ennis, TX 75119  
(214) 515-5000  
[www.polyguard.com](http://www.polyguard.com)

### PRODUCT DESCRIPTION

Fabric Tape is a rubberized asphalt waterproofing membrane laminated to polypropylene fabric backing. The membrane is wound onto a disposable silicone treated release sheet to prevent the membrane from sticking onto itself while in the roll.

### BASIC USES

Fabric Tape is used around pipe penetrations with a annular space of pipe through opening exceeding 1/2-inch, end laps and for patching damaged areas of the Blindside and Underslab waterproofing membranes.

### LIMITATIONS

Material is UV resistant and exposure should not exceed 30 days.

### TECHNICAL DATA

See physical properties table.

### INSTALLATION

Blindside and Underslab waterproofing membrane should be clean, dry and free of contaminants before application of the Fabric Tape. Apply the 650 LT Liquid Adhesive or California Sealant at a rate of 50-75 square feet per gallon to the Blindside or Underslab prior to

applying the Fabric Tape. Due to various uses of this product please see sheet membrane to be used for proper applications instructions.

### SAFETY

SDS documents for all Polyguard products can be obtained at our website [www.polyguard.com](http://www.polyguard.com). Call Polyguard Products, Inc. at (214) 515-5000 with questions.

### WARRANTY

We, the manufacturer, warrant only that this product is free of defects, since many factors which affect the results obtained from this product are beyond our control; such as weather, workmanship, equipment utilized and prior condition of the substrate. We will replace at no charge product proved to be defective within twelve (12) months of purchase, provided it has been applied in accordance with our written directions for uses we recommended as suitable for this product. Proof of purchase must be provided.

### TECHNICAL SERVICES

Technical assistance, information and Polyguard's products are available through a nationwide network of distributors and architectural representatives, or contact Polyguard Products, Inc.  
P.O. Box 755, Ennis, TX 75120-0755  
Sales: (615) 217-6061 • Tech Support: (214) 515-5000  
Email: [archtech@polyguard.com](mailto:archtech@polyguard.com)  
Website: [www.polyguard.com](http://www.polyguard.com)

PROPERTY	TEST METHOD	TYPICAL VALUE
MEMBRANE THICKNESS	ASTM D 1777	65 mils
TENSILE BREAKING STRENGTH	ASTM D 882	118 lbs/in width
TENSILE ELONGATION STRENGTH	ASTM D 882	100%
GRAB TENSILE STRENGTH	ASTM D 4632	297 lbf/in
PUNCTURE RESISTANCE	ASTM E 154	271 lbs.
WATER VAPOR TRANSMISSION	ASTM E 96 Method B	0.029 Perms
ADHESION TO CONCRETE	ASTM D 903	6.35 lbs./in. width
PLIABILITY	ASTM D 146	Pass

PACKAGING	PART NUMBER	UNIT SIZE
FABRIC TAPE	FABRIC TAPE-12	12" x 200'

**DISCLAIMER:** The information contained in this document is based on data and knowledge considered to be true and accurate at time of printing and is offered for the users' consideration, investigation and verification. Polyguard Products, Inc. cannot be held liable for errors made as a result of information herein. Changes and modifications can be made to this document without prior notice. No statement, recommendation or suggestion is intended for use which would infringe on patents or copyrights held by Polyguard Products, Inc.

