



# 363 Construction Adhesive


## PRODUCT OVERVIEW

363 Construction Adhesive is a fast tack, fast grab, low soak-in adhesive. It was especially formulated to bond polyethylene to itself, concrete block, wood, and many other hard-to-bond surfaces. Developed for the floor covering industry as a well-round-ed, general-purpose adhesive for carpet and pads. It is tinted blue so the user can readily see where it has been applied. It may also be used to bond paper, cardboard, fabric, urethane foam, foil, metal, wood, and most plastics to themselves and a variety of other substrates. It may be used either for a permanent or temporary bond.

- Spray Adhesive for all termite barrier self-adhering membranes.
- Ideal for smaller jobs and low temp applications when a gallon of 650-WB is too much or too cold for application.
- Provides a quick-tack for TRM Sealant or TRM Membranes being applied to concrete/CMU and wood surfaces.
- Yield is dependent upon surfaces, normal yield is approximately 20 square feet or sixty 2" pipe penetrations.

Property	Typical Value
Color	Light Blue
Odor	Mint When Wet
Solvent System	Hexane, Acetone, C12-C14 Isoalkanes
Propellant	DME & Hydrocarbon Blend
Bond Time	10 Seconds to 2 Minutes
Heat Resistance	Max. Service Temperature 120 F
Solids	20 % +/- 2%
Spray Pattern	Lace
VOC %	54.2
Aerosol Flammability Level	Level 3 Aerosols

## Companion Products



REV051826