



TRM Flashing

PRODUCT OVERVIEW

TRM Flashing is a non-structural pest barrier which, when properly constructed as part of the building envelope, acts as a barrier to all insects. TRM Flashing is applied where the horizontal concrete slab intersects with the exterior sheathing. This area is a frequent entry point for termites which have come up on the outside of the foundation wall.

- The only physical termite barrier with over 2 decades of university testing and has been evaluated by the ICC (Internation Code Council) against their AC 380 standard Acceptance Criteria for Termite Physical Barrier Systems.
- Strong, pliable, self-adhesive sheet flashing.
- 4-mil high density polyethylene film bonded to 36 mils of sealant = 40 mils thick.
- Formulated for low temperature application down to 30°F (-1°C).
- For flashing and seam application, available roll widths are 4", 6", 9", 12", 18". All rolls are 75' long.
- Apply around perimeter foundations, windows, sheathing seams, and door framing.
- 30-day UV exposure.

| Property | Test Method | Typical Value |
|--|--|---|
| Color | | Red/White |
| Membrane Thickness | ASTM D 1000 | 40 mils |
| Long Term Testing Against Termite Protection | ICC AC 380 | ICC AC 380 Compliance ICC ESR-3632 |
| Elongation of Barrier Sealant – Percent Stretch Before Failure | ASTM D 412 | > 1000% |
| Pesticide Repellency (Chlordane, fipronil, permethrin) | ASTM F 2130 | 0% penetration |
| Permeance to Moisture/ Water Vapor | ASTM E 96 Method B | 0.035 Grains/ft ² /hr./in |
| Tensile Strength - Film | ASTM D 882 | 5470 psi |
| Tensile Strength - Barrier Composite | ASTM D 412 Modified Die C | 325 psi |
| Peel Adhesion | ASTM D 903 | 12.1 lbs./in. width |
| Overlap Bond | ASTM D 1876 | 8 lbs./in. width |
| Low Temperature Flexibility | ASTM D 146 180° bend over 1" mandrel at -25° F (-32° C) | No cracking or delamination |
| Barrier Puncture Resistance | ASTM E 154 (Blunt Instrument) | 50 lbs. |
| Resistance to Hydrostatic Head | ASTM D 5385 | 231 ft. |

Companion Products



650 LT
Liquid Adhesive



California
Sealant



650 WB
Liquid Adhesive



Detail Sealant PW™



TRM Sill

REV121624