Safety Data Sheet

Section 1. Identification

GHS product Identifier 650 WRM

Other means of identification Not available

Relevant identified used of the substance or mixtures and uses advised against

Polymer modified bitumen membrane used for waterproofing.

Supplier's details Polyguard Products, Inc.

3801 South Interstate 45

Ennis, TX 75119

Tel: (214) 515-5000 (M-F 7 am-5 pm CST)

Emergency telephone number) with

CHEMTREC, US 1-800-424-9300 International 1-703-527-3887

hours of operation)

(24/7)

Section 2. Hazards Identification

This product is classified as a non-hazardous per OSHA 1910.1200. This product is defined as an "article". A manufactured item that is formed to a specific shape or desogn during manufacture that does not release or result in exposure to a hazardous chemical under normal use conditions.

Section 3. Composition/Information on Ingredients

Substance/Mixture Mixture **Other means of identification** Not available

Ingredient name	%	CAS#
Asphalt	50-60	8052-42-4
Distillates(petroleum), petroleum residues vaccum	5-10	68955-27-1
Distillates, petroleum, chemically neutralized heavy napthhthenic	1-5	64742-34-3
Synthetic wax	1-3	8002-74-2

The exact percentage (concentration) in the composition has been withheld as a trade secret.

Occupational exposure limits, if available are listed in section 8.

None of the components of this article are in a respirable state.

Section 4. First Aid Measures

Description of necessary first aid

measures.

Eye contact Flush with water for at least 15 minutes. If pain or irritation persists, consult a physician.

Inhalation Not likely in current form.

Skin contact Wash with soap and water. In case of irritation, consult physician.

Ingestion Not likely in current form.

Most important symptoms/effects, acute and delayed

Potential acute health effects

Eye contact May cause eye irritation

InhalationNot applicable.Skin contactIrritation and redness.

Ingestion Not known.

Section 5. Fire-Fighting Measures

Extinguishing media

Suitable extinguishing media Use an extinguishing agent suitable for the surrounding fire.

Unsuitable extinguishing media None known

Specific hazards arising from theGeneration of toxic fumes from burning product.

chemical

Special Fire Fighting Procedures For large fires in confined area, use approved self-contained breathing apparatus

(SCBA). Use water fog or spray to protect exposed equipment and containers.

Section 6. Accidental Release Measures

Personal precautions, protective equipment, and emergency procedures.

For emergency respondersNo special measures required.

Methods and materials for containment and cleaning up

Spill Due to the physical state of this material, spills are not possible.

Section 7. Handling and Storage

Precautions for safe handling

Protective measuresDon appropriate personal protective equipment (see Section 8). Avoid exposure-obtain

special instructions before use. Do not handle until all safety precautions have been read and understood. Do not get in eyes. Do not swallow. Store away from heat, sparks, open

flames, and other ignition sources.

Advice on general occupational

hygiene

Eating, drinking, and smoking should be prohibited in areas where material is handled, stored, and processed. Workers should wash hands and face before eating, drinking, and

smoking. See section 8 for additional information on hygiene measures.

Condition for safe storage including

any incompatibilities

Store in accordance with local regulations. Store protected from direct sunlight in a dry cool and well-ventilated area, away from incompatible materials (see section 10) and

food and drink. Eliminate all ignition sources.

Section 8. Exposure Controls/Personal Protection

Occupational exposure limits

Ingredient name	Exposure limits		
Asphalt	NIOSH REL		
	CEIL: 5 mg/m ³ 15 minutes. Form: fume		
	ACGIH TLV		
	TWA: 0.5 mg/m ³ , (inhalable fume)		
Synthetic wax	OSHA		
	TWA- 2 mg/m ³ (fumes)		
	ACGIH TLV		
	$TWA-2 mg/m^3$ (fume)		
	NIOSH REL		
	TWA: 2 mg/m ³ (fume)		

Appropriate engineering controls

No special ventilation requirements. Ventilation should be sufficient to control worker exposure to airborne contaminants.

Environmental exposure controls

Emissions from ventilation or work process equipment should be checked to ensure they

COI

comply with the requirements of environmental protection legislation.

Hygiene measure

Wash hands, forearms, and face thoroughly after handling chemical products, before eating, smoking, and using the lavatory and at the end of the working period. Ensure that eyewash stations and safety showers are close to the workstation location.



Section 8. Exposure Controls/Personal Protection

Eye/face protection Safety eyewear complying with an approved standard should be used when risk

assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases

and dusts.

Skin Protection

Hand protection Chemical- resistant, imprevious gloves complying with an approved standard should be

worn at all times when handling chemical products if a risk assessment indicates this is

necessary.

Body protection Personal protective equipment for the body should be selected based on the task being

preformed and the risks involved and should be approved by a specialist before handling

this product.

Other skin protection Appropriate footwear and any additional skin protection measures should be selected

based on the task being preformed and the risks involved and should be approved by a

specialist before handling this product.

Respiratory protectionBased on the hazard and potential for exposure, select a respirator that meets the

appropriate standard or certification. Respirators must be used according to a respiratory protection program to ensure proper fitting, training, and other important aspects of use.

Section 9. Physical and Chemical Properties

Appearance

Physical state Solid

Color White printed backing/ Black adhesive layer.

Odor Asphaltic(slight) **Odor threshold** Not available pН Not applicable **Melting point** Not available **Boiling point** Not applicable **Flash Point** Not determined **Evaporation rate:** Not applicable Flammability (solid, gas) Not applicable Lower & upper explosive Not applicable

(flammable) limits

Vapor density Not applicable Vapor pressure Not applicable

Relative density 1.09

SolubilityInsoluble in waterPartition coefficient: n- octanol/waterNot availableAuto- ignition temperatureNot applicableDecomposition temperatureNot applicableViscosityNot applicable

VOC 0 g/l

Section 10. Stability and Reactivity

ReactivityChemical stability
No data available.
This product is stable.

Possibility of hazardous reactions Under normal conditions of storage and use, hazardous reactions will not occur.

Conditions to avoid: No data available

Incompatible materials Reactive or incompatible with the following materials: Oxidizing materials

Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should

not be produced.



Section 11. Toxicological Information

Information on toxicological effects Acute toxicity

Product/ingredient name	Result	Species	Dose	Exposure
Petroleum Asphalt	LD50 Oral	Rat	> 5000 mg/kg	-
	LD50 Dermal	Rabbit	> 2000 mg/kg	-
Distillates, petroleum,	LC50 Oral	Rat	> 5000 mg/l	-
chemically neutralized heavy	LD50 Dermal	Rabbit	> 2000 mg/kg	-
napththenic				
Synthetic wax	LD50 Oral	Rat	>5000 mg/kg	-
	LD50 Dermal	Rabbit	> 3600 mg/kg	-

Irritation/Corrosion Sensitization Mutagenicity There is no data available There is no data available There is no data available

Carcinogenicity Classification

Product/ingredient name	OSHA	IARC	NTP
Asphalt	-	2B	-
Distillate, Petroleum , chemically	-	1	known
neutralized heavy naphthenic			

Section 12. Ecological Information

Toxicity

Persistence and degradability Bioaccumulative potential There is no data available There is no data available

Mobility in soil

Soil/water partition coefficient (K_{OC})

There is no data available.

Other adverse effects

No known significant effects or critical hazards

Section 13. Disposal Considerations

Disposal methods

The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe way. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor.

Section 14. Transportation Information

AERG: Not applicable

Regulatory Information

Information:

DOT/TDG/IMDG/IATA Not regulated



Section 15. Regulatory Information

U.S. Federal regulations: United States inventory (TSCA): all components are listed or exempted

Composition/information on ingredients

SARA 304 RQ Not applicable
SARA 311/312 Not applicable
SARA 313 Not applicable

State regulations

MassachusettsThe following components are listed: Petroleum asphalt, Synthetic waxNew JerseyThe following components are listed: Petroleum asphalt, Synthetic waxPennsylvaniaThe following components are listed: Petroleum asphalt, Synthetic waxCalifornia Prop.65None of the components are listed on the Prob 65 list dated 12-29-2023.

16. Other Information

Date of revision: 12/17/2024
Date of previous issue N/A

Revisions: New product

Version 1

Prepared by C. Rogalski

Notice to reader: To the best of our knowledge, the information contained herein is accurate. However, neither the above-named supplier nor any of its subsidiaries assumes any liability whatsoever for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.