



Butyl Flash

PRODUCT OVERVIEW

Butyl Flash Window Flashing Tapes are used to strip in or flash straight window frames, door frames, and other construction seams. Butyl Flash is suitable for both hot and cold temperature ranges, down to 15°F. It is a self-adhering, self-sealing flashing tape consisting of a butyl-based waterproofing coating, laminated to polyethylene film. The flashing is supplied in rolls, with an easy to remove film release liner and is available in 20 mil thickness and a variety of roll sizes.

- Works in cold temperatures, down to 15° F
- Withstands performance temperatures up to 240°F
- Available in 4", 6", 9", and 12" widths
- Rolls are 100 linear feet
- Self-seals: Providing a smooth watertight surface around nails, staples, and fasteners
- Easy peel and stick tape supplied in rolls with an easy to remove release liner for mess free application
- Superior adhesion
- When installed correctly, will prohibit mold and mildew in sub-surfaces

Test	Result	Minimum Requirement - Pass/Fail
Tensile Strength		Pass
Water Penetration Resistance around Nails - Prior to Thermal Cycling	No Water in Bottom Can, on Nail Shanks or on the Underside of the Sheathing - PASS	No Water in Bottom Can, on Nail Shanks or on the Underside of the Sheathing - PASS
Water Penetration Resistance around Nails - After to Thermal Cycling	No Water in Bottom Can, on Nail Shanks or on the Underside of the Sheathing	No Water in Bottom Can, on Nail Shanks or on the Underside of the Sheathing
90° Peel Adhesion on OSB	3.2 lbs./in.	1.5 lbs./in. - PASS
Cold Temperature Pliability	No visible signs of cracking	No visible signs of cracking - PASS
Self-Resistance to Peeling	No Peeling	Report Only - PASS
Thickness (mils) (+-.05)	22 mils	
Water Vapor Transmission ASTM E 96 (Method B)	0.14 Perms	
Peel Adhesion to Primed Steel ASTM D 1000	6.1 lbs./in. width	
Elongation - Ultimate Failure or Rubberized Asphalt ASTM D 412 (Modified Die C)	M-400% T-291%	
Softening Point ASTM D36	Estimate range 180-200°F	
Low Temperature Pliability ASTM D 146 (Modified)		Pass

REV053024

COMPANION PRODUCTS

