



polyguard

RESIDENTIAL

ClearBond Liquid Adhesive

PRODUCT OVERVIEW



CLEARBOND LIQUID ADHESIVE is a rubber based adhesive in solvent solution formulated to improve adhesion of Polyguard construction flashing tapes, below-grade sheet waterproofing membranes, and above-grade sheet air barrier membranes. It is specifically suited for use in cool weather when rubberized asphalt tapes tend to have poor adhesion performance. CLEARBOND LIQUID ADHESIVE is clear in appearance.

- Used to prime structural surface where Polyguard below-grade and above-grade sheet membranes may be installed
- Designed to be used on applications where ambient and/or surface temperature is above 25°F (-4°C)
- Compatible with concrete, masonry, or wood surfaces

APPLICATION:

CLEARBOND LIQUID ADHESIVE may be applied with roller or brush. Should be used on vertical surfaces. Can be used on horizontal surfaces, but product remains tacky and precautions must be used in this application. Apply CLEARBOND LIQUID ADHESIVE to a clean, dry, dust free, and frost free surface at a coverage of approximately 250 to 300 square feet per gallon. The liquid adhesive should be spread sufficiently. Areas of excess material will lengthen curing time.

For best results CLEARBOND LIQUID ADHESIVE should be applied and allowed to become tacky to touch, timing may vary due to atmospheric conditions. At this point the tape or flashing should be applied over the primed surface(s). Cover the open containers between applications of liquid adhesive. If adhesive dries on the substrate surface(s), so is no longer tacky, then re-apply new adhesive over the existing dried-out adhesive and allow the new adhesive to become tacky for proper sheet membrane overlay adhesion / bond.

REV042624