



Home Stretch Detail Tape

PRODUCT OVERVIEW

Home Stretch™ Detail Tape is a strong, pliable, self-adhesive sheet consisting of a cross-laminated, high-density polyethylene (HDPE) backing bonded to a rubberized asphalt compound. Poly Wall® Home Stretch™ Detail Tape is used to fabricate inside and outside corners, seal penetrations, control joints, cold joints and to patch damaged areas of Home Stretch™ Waterproofing Membrane. Home Stretch™ Detail Tape is available in easy to handle and install 12" wide by 66.7' long rolls with a disposable treated release liner.

- 12" x 66.7' rolls for detailing
- Factory controlled 40-mil uniform and consistent thickness
- Side lap design delivers increased water tightness
- Extended selvage edge provides asphalt-to-asphalt adhesion at the seam
- Appropriate for use with both Expanded and Extruded Polystyrene ICF Systems
- High Tensile Strength with terrific flexibility
- No VOCs, no odor
- Release film does not tear easily and protects adhesive layer

Test	Result	Minimum Requirement - Pass/Fail
Membrane Thickness	ASTM D 1000	40 mils
Tensile Strength - Membrane	ASTM D 412 Modified Die C	370 PSI
Elongation - Ultimate failure of rubberized asphalt	ASTM D 412	600%
Tensile Strength (Film	ASTM D 882	7294 psi
Permeance	ASTM D E96 Method B	0.002 Perms
Crack Cycling	ASTM C 836 Test @ 15°F (-26°C)	No effect
Peel Adhesion	ASTM D 903	17 lbs./in. width
Lap Peel Adhesion	ASTM D 1876	8.0 lbs./in./width
Low Temperature Flexibility (-15°F)	ASTM D 1970 Modified	Pass
Pliability	ASTM D 146 180° bend over 1" mandrel at -25°F (-32°C)	No effect
Puncture Resistance - Membrane	ASTM E 154	69 lbs.
Resistance to Hydrostatic Head	ASTM D 5385	>231 ft.
Exposure to Fungi in Soil	GSA-PBS 07115 (16 weeks)	No effect
Water Absorption	ASTM D 570	0.1%

REV062824

COMPANION PRODUCTS

