

Blue Barrier 2300

Product Overview



Blue Barrier™ Liquid Wrap 2300 is a low VOC spray applied, fully adhered, permeable, air and moisture building envelope protection membrane. This thin mil, seamless substrate coating can be applied with an approved airless sprayer or power rolled. Liquid Wrap can be sprayed over clean and debris free surfaces and substrates such as OSB, plywood or exterior gypsum.



Superior substitute for traditional housewraps



Exceptional adhesion, bonds to multiple substrates (OSB, plywood, gypsum, CMU)



Permeable; allows substrates to breathe



Damp surface application, bonds and cures in damp conditions



Stands up to UV for up to 9 months of UV Exposure



Can be covered with commonly used cladding/siding systems including heavy veneers



When utilized with our Blue Barrier 2200 Joint Filler combines to fill in voids up to 3/4" due to penetrations or dissimilar surfaces



Class A surface burning rated: Provides added fire protection against flame spread and smoke development

Typical Properties - Cured Properties at 21 days

NFPA 285	Compliant under many wall assemblies
Hardness, Shore A	40-45
Tensile Strength	90-100 psi
Elongation	225-300%
Tear Strength	50-60 psi
Perm Rating	15 Perms
Solids Content	90% Solids
UV Exposure	6 months
Uncured Properties	
Tack Free Time	<60 minutes
Cure Rate	1/8" - 16hrs.
VOC Content	<20 g/l

Companion Products



contact us

3801 S. IH-45
Ennis, TX 75119

Phone : 214-515-5000

Web : www.polyguard.com

Social : @polyguardproducts

