

Blue Barrier 2400

Product Overview



Blue Barrier Flash 'N Wrap 2400 is designed as a liquid applied Window & Door Flashing. Easily applied with a roller Flash 'N Wrap 2400 replaces traditional Window Tapes utilizing the latest in Silyl Terminated Polyether Technology (STPE). No more worry about your tape sticking or tearing when your window is installed. Dries quickly to a tough, permeable, continuous membrane that is durable enough to withstand installation of even the heaviest window or door and protect your investment for years to come. Flash 'N Wrap can be roller applied over prepared surfaces and substrates. Coverage rate is 64 SF/Gallon/25 mils wet for window and/or door flashing applications. Available in 2-gallon and 5-gallon pails.



Ideal viscosity for both roller and brush applications



Finished product produces durable seamless membrane



Damp surface application, bonds and cures in damp conditions



Tenacious adhesion to rough opening and exceptional durability



Single stage product, no mixing needed



One step application, no primer required



Permeable/Allows substrates to breathe



Class A surface burning rated: Provides added fire protection against flame spread and smoke development

Typical Properties - Cured Properties at 21 days

NFPA 285	Compliant under many wall assemblies
Hardness, Shore A	45
Tensile Strength	100 psi
Elongation	300%
Tear Strength	50-60 PSI
Peel Strength	25 PLI
Perm Rating	23 Perms
UV Exposure	9 months when used as window/door flashing
UV Exposure	9 months when used as an air barrier
Uncured Properties	
Tack Free Time	<60 minutes
Cure Rate	1/8" - 16hrs.
VOC Content	23 g/l

Companion Products



contact us



3801 S. IH-45
Ennis, TX 75119

Phone : 214-515-5000

Web : www.polyguard.com

Social : @polyguardproducts

