



RG-2400 - Product Matrix

		Minimum Temperature	Maximum Constant Temperature	Chilled Water	Sub-Freezing Systems (ammonia, glycol, brine)	In-Service Hot Application (150F-200F)	High Temp Service (up to 350F)	Spray Application	Structural Steel	Tank Chimes	COLD VESSELS	HOT VESSELS	Notes:
STANDARD GEL PRODUCTS	RG-2400 LT Low Temperature service gel	None	250° F	2	1	3	4	1	3	3	1	3	Temp Range 250°F Gels do not cure and have to be protected.
	RG-2400 AK In-service hot applications and tank chime installation	None	250° F	2	2	1	4	3	3	1	2	2	Temp Range 250°F - good for application on in-service HOT lines
	RG-2400 ET High temperature service	None	350° F	3	2	2	1	2	3	2	3	1	Temp Range 350°F Gels do not cure and have to be protected
SPECIALTY PRODUCTS	RG-CHW Designed for chilled water only	33° F	110° F	1	4	4	4	2	3	4	4	4	Temp Range 40° F - 100° F <u>DO NOT FREEZE</u>
	RG-CSA Primer Not a Gel Product, will harden	-20° F	200° F	N/A				1	1	N/A		2	Hardening primer coat for structural steel and uninsulated vessels
	RG-CSA Top Coat Not a Gel Product, will harden	-20° F	200° F	N/A				1	1	N/A		2	Hardening topcoat for structural steel and uninsulated vessels (can be tinted)
	RG-2400 AL MIC RG gel for aluminum piping	-40° F	200° F	1	1	2	4	1	N/A		1	1	94% effective against MIC corrosion on Aluminum piping systems
	RG-2401 Down Hole Oil Well Corrosion Gel	None	250° F	N/A									Used for annular space corrosion control where specific gravity is an issue
MISC PRODUCTS	RG Cleaner Cleaner Designed for gels	35° F	150° F	2	1	1	2	N/A			1	1	Cleaning of tools, spills, spray equipment
	GeoWrap Geotextile for high temp uses	-40° F	350° F	2	1	1	2	N/A			1	1	Used to keep the insulation clean for inspection cycles
	UV Wrap UV wrap for small uninsulated pipes	-40° F	150° F	2	2	4	3	N/A					Spiral wrap UV stretch film for protecting RG on small diameter uninsulated piping
	Alumaguard Lite (no adhesive) Weather Barrier Protection for RG	-40° F	200° F	1	1	2	3	N/A		1	1	2	For uninsulated small diameter pipes to protect from UV, dirt, and personnel
	AccuTrowel Tools to Install RG Accurately	N/A		1	1	1	1	N/A					Tool Set custom designed for 2" - 12" Pipes to apply gel at 25 MIL thickness

1 = BEST	2 = GOOD
3 = NOT RECOMMENDED	4 = WILL FAIL

WWW.POLYGUARD.COM

214-515-5000

