



- ① FIRST COURSE OF MASONRY (BRICK SHOWN) WITH TERM[®] WEEP/VENT BARRIER, INSTALLED WITH THE MESH BARRIER FACING OUT IN THE FLASHED COURSE. WEEP CAN BE INSTALLED VERTICALLY (SHOWN) OR HORIZONTALLY AT LESS-THAN-OR-EQUAL-TO 33" SPACING
- ② MORTAR BLOCKING / CAVITY DRAINAGE PROTECTION, INSTALLED MINIMUM 12" HIGH AND EQUAL IN DEPTH TO THE CAVITY DIMENSION
- ③ MASONRY, BRICK SHOWN
- ④ TERM[®] WEEP/VENT BARRIER, INSTALLED WITH THE MESH SIDE FACING OUT INTO THE MASONRY COURSE CLOSEST TO 12" ABOVE THE BASE FLASHING COURSE

TM3 TERM[®] WEEP / VENT BARRIER IN MASONRY WALL - INSTALLATION SEQUENCE

© POLYGUARD PRODUCTS, INC.

P.O. Box 755 - Ennis, TX 75120
 Phone: 214-515-5000 Fax: 972-875-9425
 Web Site - www.polyguardbarriers.com



polyguard
 TERM BARRIER

The information provided is based on data and knowledge considered to be true and accurate and is offered for the users' consideration, investigation, and verification; but we do not warrant the results to be achieved. Please read all data sheets, statements, suggestions, or recommendations in conjunction with our conditions of sale, which apply to all goods supplied by us.

DRAWING SCALE:	NOT TO SCALE
EFFECTIVE DATE:	06/12/2020
SUPERCEDES:	NONE